



4G LTE USB WIFI (UFI)



SoC	ASR1803S CAT4 / ASR5803W	
Dimension	90.5*28.6*12mm	
Bands	LTE FDD B1/3/5/7/8/20/28AB, TDD B38/39/40/41, WCDMA 900/2100MHz (Bands support to be customized)	
Form factor	USB Stick	
Battery	NA	
Wi-Fi	802.11 b/g/n, WIFI speed up to 72Mbps, max 10 users connection	
Working	Plug and Play	
Data Rates	LTE CAT4 FDD-LTE 150Mbps DL /50Mbps UL	
Hardware	USB	USB2.0, Type A
	SIM	2FF (eSIM / VSIM optional)
	LED	Network Indication and Signal strength
	Antenna	Build-in FPC type
	Power Consumption	LTE/WCDMA <2.5W
	Power	USB DC 5V
	Voltage	
	Reset	Pinhole
	Update	FOTA & Local update
	Support OS	Compatible with Windows / MACOS / Linux / Android
Software		IPv4/IPv6, SMS, Phonebook, SIM Lock, Firewall, Data statistics,
	Others	WIFI Security
Operation Temperature	Operation Temperature: -10 to 55°C / Operation Humidity: 10% to 80%	
	Storage Temperature: -40 to 85°C / Storage Humidity: 5% to 95%	



Model:D140

- ✓ LTE Cat4 ASR1803S Cost effective Solution
- ✓ eSIM / VSIM optional