

Pixel Pitch

P0.78125

P0.9375

P1.25

P1.5625

Packaging type	Inversion	Inversion	Inversion	Inversion
Physical density (Dot/sqm)	1638400	1137778	640000	409600
Module resolution	192X216	160X180	120X135	96X108
Module size (mm)	150X168.75	150X168.75	150X168.75	150X168.75
Panel Dimension (WXHXD/mm)	600X337.5X27.5	600X337.5X27.5	600X337.5X27.5	600X337.5X27.5
Panel Resolution	768X512	640X360	480X270	384X216
Module QTY (WXH)	4X2	4X2	4X2	4X2
Panel weight (kg)	4.5	4.5	4.5	4.5
Maintenance Mode	Front maintenance	Front maintenance	Front maintenance	Front maintenance
Cabinet Material	Die-casting aluminum	Die-casting aluminum	Die-casting aluminum	Die-casting aluminum
Brightness Calibration	Have	Have	Have	Have
Brightness (Nits)	≥600	≥600	≥600	≥600
Color temperature (K)	1000-18500 Optional	1000-18500 Optional	1000-18500 Optional	1000-18500 Optional
Viewing angle (V/H)	170° /170°	170° /170°	170° /170°	170° /170°
Brightness/Color uniformity	≥99.8%	≥99.8%	≥99.8%	≥99.8%
Contrast ratio	10000 : 1	10000 : 1	10000 : 1	10000 : 1
Frame frequency	50/60	50/60	50/60	50/60
Drive mode	48-96 scan	1/60 scan	1/60 scan	1/48 scan
Grey level	16bit	16bit	16bit	16bit
Refresh rate (Hz)	3840	3840	3840	3840
Max. power consumption (W/sqm)	420	420	420	420
Avg. power consumption (W/sqm)	80-150	80-150	80-150	80-150
Protection level	IP31	IP31	IP31	IP31
Power input	AC90-264V, 47-63Hz			
Working temperature/humidity (°C/RH)	-20~60°C/10%~85%			
Storage temperature/humidity (°C/RH)	-20~60°C/10%~85%			
Certification	CCC/CE/RoHS/FCC/CB/TUV/IEC			