


开口型沉头抽芯铆钉

Open Type C' SUNK Bind Rivets

可生产5.0、6.0的规格

Dia.5.0、6.0 are available



GB12617

材质:304不锈钢、316不锈钢、碳钢、铝合金、铜 Material: 304/316 stainless steel, steel, aluminum , Brass							单位 (unit):mm
铆钉规格 Rivet Size	产品编号 Part Number	长度 Length	铆接范围 Grip Range	帽径 Head Dia	帽厚 Head Height	钉芯直径 Mandrel Dia	孔径 Hole size(Drill)
D		L		dk	K	dm	φ
2.4 +0.08 -0.15	2404	4.0	0.5-2.0	4.2-5.0	1.0	1.6	2.5-2.6
	2406	6.0	2.0-4.0				
	2408	8.0	4.0-6.0				
	2410	10.0	6.0-8.0				
	2412	12.0	7.0-9.5				
	2414	14.0	8.0-11.5				
3.0 +0.08 -0.15	3006	6.0	1.0-3.5	5.4-6.3	1.3	2.0	3.1-3.2
	3008	8.0	3.5-5.0				
	3010	10.0	5.0-7.0				
	3012	12.0	7.0-9.0				
	3014	14.0	9.0-11.0				
	3016	16.0	9.0-12.5				
3.2 +0.08 -0.15	3205	5.0	1.0-2.5	5.8-6.7	1.3	2.0	3.3-3.4
	3206	6.0	1.0-3.5				
	3208	8.0	3.5-5.0				
	3210	10.0	5.0-7.0				
	3212	12.0	7.0-9.0				
	3214	14.0	9.0-11.0				
4.0 +0.08 -0.15	4016	16.0	9.0-12.5	6.9-8.4	1.7	2.5	4.1-4.2
	4006	6.0	1.0-3.0				
	4008	8.0	3.0-5.0				
	4010	10.0	4.0-6.5				
	4012	12.0	6.0-8.5				
	4014	14.0	7.0-10.5				
	4016	16.0	8.0-12.5				
	4018	18.0	10.0-14.5				
	4020	20.0	12.0-16.0				
	4025	25.0	16.0-21.0				
4.8 +0.08 -0.15	4830	30.0	21.0-25.0	8.3-10.1	2.0	3.0	4.9-5.0
	4835	35.0	25.0-30.0				
	4840	40.0	30.0-35.0				
	4806	6.0	1.0-2.5				
	4808	8.0	2.5-4.0				
	4810	10.0	4.0-6.0				
	4812	12.0	6.0-8.0				
	4814	14.0	8.0-10.0				
	4816	16.0	8.0-12.0				
	4818	18.0	10.0-14.0				
	4820	20.0	12.0-16.0				
	4825	25.0	16.0-21.0				
6.4 +0.08 -0.15	6430	30.0	18.0-23.0	11.6-13.4	2.7	4.2	6.5-6.6
	6418	18.0	8.0-12.0				
	6420	20.0	10.0-14.0				
	6025	25.0	14.0-18.0				
	6414	14.0	6.0-8.0				
	6416	16.0	6.0-10.0				
	6410	10.0	2.0-4.0				
	6412	12.0	3.0-6.0				