



SHENZHEN SIGTECH TECHNOLOGY CO.,LTD

Add: Floor 5, Mingfeng Building, No.2 Xikeng Rd, Xinhe Village, Fucheng Town, Longhua Dist, Shenzhen, China
 Mobile: +86-13826547281 Skype: dennyliao2 E-Mail: sales@sigtechgifts.com



Image	Item	Specification
	Main function	GPS/AGPS/Wifi/LBS location, 2 ways SOS, remote monitoring, family Number, Fence, historical track playback, Alarm, Sound callback, Class mode, power saving
	Chipset	MT6261 + AT6558R + MTK5931
	Memory	32M Flash Memory
	RF power amplifier	RDA6625E
	Dimension	54*85.5*7.2mm
	Working temperature	-20℃ - +70℃
	Working environment humidity	20%-80%RH
	SIM slot	Nano SIM
	GSM network	850MHz/900MHz/1800 MHz/1900MHz
	GPRS	Class 12
	Battery	default 3.7V 1500mAh rechargeable Li-polymer battery(adjustable according to your requirement)
	Average standby current	2-6ma
	I/O	Micro 5pin USB
	Speaker	0916 AAC
	MIC	HD silicone microphone
	Montion sensor	3D G-Sensor
	Memory slot	No
	GPS locaiton accuracy	within 10 meters outdoor
	WIFI location accuracy	within 50 meters
	LBS location accuracy	50-200 meters (depend on your local telcom operator network status)
Speed accuracy	0.1m/s	
GPS location time	Cold Boot-38s(Open field), Warm Boot2s(Open field), The specific time is affected by the environment	
Housing	PC	
GSM antenna	PIFA	
Standby time	above 10 days(on base of 10 minutes interval)	
Working voltage	3.5-4.2V (below 3.4V will power off automatically)	
Recharging current	5V 500mAh-1000mah	
GPS antenna	High gain 15X15mm ceramic GPS antenna	