


Thermal transfer printer series

Model: CH421

4 inch thermal transfer printer



Specification:

Printing Method	Thermal Transfer Printing/Thermal Printing
Printing Speed	100mm/s(max)
Resolution	203dpi/300dpi
Character Set	Support User-defined characters GB18030 24X24 ASCII 9X17,12X24
Graphics printing	support dots printing with different densities,support raster bitmap print,support downloaded bit image print
Code pages	support simplified&traditional Chinese ,English,Japanese and other 45 kinds of international character sets.
Barcode type	UPC-A;UPC-E;JAN13(EAN13);JAN8(EAN8);CODABAR; ITF;CODE39;CODE93;CODE128;QR CODE;
Interface	USB+Ethernet+Bluetooth+WiFi
Power	DC 24V/2.0A
Cashbox control	RJ11-6P6C Socket,24V
Work environment	Temperature: 0~45°C; Dampness:10~80%
Storage environment	Temperature: -10~60°C; Dampness:10~90%
Paper Width	40-108mm
printing width	108mm(MAX)
Max diameter of paper roll	100mm
Paper cutting	manual/with auto-cutter(optional)
Dimension(L*W*H)	227mmx179mmx161mm
TPH life	100km
paper type	thermal label paper, PET paper, Coated paper
Drivers:	Windows(WIN7/WIN8/WIN10/Vista/XP/2000) Ubuntu 12.04 32/64 Ubuntu 14.04 32/64 MAC OS
Printing command	Compatible with ESC/POS/JPL/TSPL/CPCL/EPL/ZPL command set
Ribbon diametre	less than 65mm
Ribbon length	300m
Ribbon width	110mm
Ribbon type	Wax-based, mixed-base, resin-based

Feature

- ★ Easy paper loding ,Exquisite design and easy to use
- ★Support label paper and continuous paper printing
- ★ High speed、 high life、 high quality、 low repair rate, apply to all sorts of business software
- ★Low noise, high-speed printing
- ★Support WPS printing
- ★Support paper end detection, seam detection, black label detection, open cover detection, and paper removal detection
- ★Easy to use and maintain
- ★USB, network port, Bluetooth, WiFi multiple interfaces with communication

Application:

- ◆ Food Industry
- ◆ Retail Supermarket
- ◆ Medical Industry
- ◆ Product Packaging
- ◆ Logistics Industry
- ◆ Manufacturing
- ◆ Warehousing

