



# SPECIFICATION

| MODEL                    | MCL 940                      |                             |
|--------------------------|------------------------------|-----------------------------|
| ENGINE                   | Engine Model                 | Yun Nei 4102 Supercharged   |
|                          | RPM                          | 2400                        |
|                          | Rated Power                  | 76 kW                       |
|                          | Emissions                    | EU Stage II                 |
| WEIGHTS                  | Operating Weight             | 6100 kg                     |
|                          | Rated Load                   | 2800 kg                     |
| BUCKETS                  | Bucket Capacities            | 1.2 m <sup>3</sup>          |
| TRANSMISSION             | Max. Travel Speed            | 28 km/h                     |
|                          | Gear Box                     | CVT<br>280 torque converter |
|                          | Axle                         | Large hub                   |
|                          | Axle Base                    | 2560 mm                     |
|                          | Brake                        | Disc Brake                  |
| HYDRAULIC SYSTEM         | Hydraulic Cycle time - lift  | ≤ 6 s                       |
| DIMENSIONS(APPROXIMATE)  | Min. Ground Clearance        | 400 mm                      |
|                          | Wheel Base                   | 1640 mm                     |
|                          | Reach at Max.Dump Height     | 3600 mm                     |
|                          | Dump Reach                   | ≤ 650 mm                    |
|                          | Overall Length - With Bucket | 6240 mm                     |
|                          | Overall Width                | 2040 mm                     |
|                          | Overall Height               | 2830 mm                     |
| OPERATING SPECIFICATIONS | Tyre Size                    | 1670-24                     |
|                          | Joystick                     | Machanical                  |
|                          | Min. turning radius          | ≤ 6200 mm                   |
| STANDARD EQUIPMENT       | Hour meter                   | Yes                         |
|                          | Tool Box                     | Yes                         |
|                          | Dual Hight&Low Speed Handle  | Yes                         |
| OPTIONAL EQUIPMENT       | Air Conditioning/heater      |                             |
|                          | Quick Change                 |                             |
|                          | Multifunctional Attachment   |                             |
|                          | Hydraulic Pilot              |                             |