






SPECIFICATIONS:

Rated Current	3.0AMP
Contact Resistance	20mΩ Max
Withstand Voltage	1000V AC/DC
Insulation Resistance	1000mΩ Min
Operation Temperature	- 40°C to +105°C
Contact Material	Brass
Contact Plating	Au over Ni
Insulator Material	PA6T
Max. Processing Temp:	230°C for 30-60 seconds 260°C for 10 seconds


Recommended P.C.B Layout(Top Side)
 (PCB BOARD TOLERANCE±0.05)


Dimension antitheses list				
ITEM	PA	PB	PC	L
Standard	6.00	4.40	3.00	14.0
Alternate				

Ordering Information

HC Series	No. of Pin Per Row	Insulator Option	N	Plating	Type	PIN Length	Packing	End code
HC-PH42511 2.54mm Pin Header	1x01P	A=PBT		G0=Gold Flash	R=Right Angle	L=XXX	0=PE Bag	02
	1x40P	B=PA66		SN=Tin Plated		Confirm you	A=Tray	
		C=PA6T		SM=Matted Tin		need size of	T=Tube	
		D=PA46		S0=Gold/Tin		PA/PB/PC	P=Tube+Cap	
		E=PA9T		G1=3u Gold			R=Reel+Cap	
		F=LCP		G2=5u Gold			M=Reel+Mylar	
		X=Special		G3=10u Gold			X=Special	
				G4=15u Gold				
				G5=30u Gold				
				S1=3u Gold/Tin				