

|                                  |                                                                                                                                                                                                         |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Model</b>                     | <b>U141 4G Ufi</b>                                                                                                                                                                                      |
| ID Picture                       |                                                                                                                       |
| SoC                              | ASR1803S CAT4 / ASR5803W                                                                                                                                                                                |
| Dimension                        | 95*31*10mm                                                                                                                                                                                              |
| Bands                            | LTE FDD B1/3/5/7/8/20/28AB, TDD B38/39/40/41, WCDMA 900/2100MHz ( The other bands can be customized, and prices will be negotiated.)                                                                    |
| Form factor                      | USB Stick                                                                                                                                                                                               |
| Wi-Fi                            | 802.11 b/g/n, WIFI speed up to 72Mbps, max 10 users connection                                                                                                                                          |
| Working                          | Plug and Play                                                                                                                                                                                           |
| Data Rates                       | LTE CAT4 FDD-LTE 150Mbps DL /50Mbps UL                                                                                                                                                                  |
| Hardware                         | USB2.0<br>Type A SIM 2FF (eSIM / VSIM optional)<br>Network Indication and Signal Strength LED<br>Built-in FPC-type Antenna Power Consumption: LTE/WCDMA <2.5W<br>Power Voltage: USB DC 5V Pinhole Reset |
| Software                         | FOTA & Local update<br>Compatible with Windows / MACOS / Linux / Android IPv4/IPv6, SMS, Phonebook, SIM Lock, Firewall, Data statistics, WIFI Security                                                  |
| Operation Temperature and        | Operation Temperature: -10 to 55℃ Operation Humidity: 10% to 80%                                                                                                                                        |
| Storage Temperature and humidity | Storage Temperature: -40 to 85℃ Storage Humidity: 5% to 95%                                                                                                                                             |