









ABIDE BY WEEE & ROHS





- Specification :
- 1. Rating: 12V AC/DC max. 2V DC min. 10mA AC/DC max. 10 μ A DC min.
 - 2. Contact Resistance: 200m Ω Max
 - 3. Insulation Resistance: 100M Ω Min. (DC100V)
 - 4. Withstand Voltage: AC100V(50-60Hz) for 1 minute
 - 5. Tactile Force: 60 $\pm$ 10gf
 - 6. Operation Force: 50 $\pm$ 15gf
 - 7. Return Force: $\geq$ 15gf
 - 8. Conduction travel: 1.80 $\pm$ 0.4mm
 - 9. Total travel: 3.60 $\pm$ 0.3mm
 - 10. Electrical Life: 50,000,000 Cycles(min).
 - 11. Degree of protection: IP54(Only for the electrical functional Box sealed part)
- <Feel is allowed to have difference before and after life test>

■ 电路图



■ 轴倾斜角度



⑪	Torsional Spring	—	1	Stainless Steel	Nature	—
⑩	Light guide	—	1	PC	Fogtransparent	—
⑨	Base	—	1	POM	Orange	—
⑧	Slider	—	1	POM	Green	—
⑦	Protecting Cover	—	1	Nylon	White	—
⑥	Spring	—	1	Stainless Steel	Nature	—
⑤	Contact	—	2	Composite gold	—	—
④	Cover	—	1	POM	Orange	—
③	Keystroke	—	1	POM	Nature	—
②	Static Plate	—	1	Brass	Sn over Ni-plating	—
①	Movable Plate	—	1	Copper Alloy	Nature	—
ITEM	PART NAME	TER'NO.	QTY.	MATERIAL	FINISHING	REMARK

APPROVALS

DATE

DRAWN ZhangTaiPing

2024. 05. 30

CHECKED



东莞市凯华电子有限公司
KAIHUA ELECTRONICS CO., LTD

TITLE:

PG1511F Keystroke Switch

APPROVALS

PART NO:

CPG1511F01S259

TOLERANCES
ARE

30<L ±0.30
10<L ≤30 ±0.20
5<L ≤10 ±0.15
L ≤5 ±0.10

ANGLE

UNIT: mm

SCALE: 1:1

PROJ:

ECN NO.

REV.

DATE.

DESCRIPTION.

CHANGE.

CHECK.

APPRO.

DRAWING NO.

KHA-PG1511F-279EN

SHEET: 1 OF 1




凱華電子
KAILH ELECTRONICS

Document Number:

KH-PS2405-37

产品规格书

Product Specification



P/N: CPG1511F01S259			Title : PG1511F Keyboard Switch		
Rev.	ECN	Release and Revision Description:	Prepared By /Date:	Checked By/Date:	Approved By/Date:
A	— —	New releasing 初版发行	张太平/2024.05.28	吕攀豪/2024.05.28	张华昌/2024.05.28

	Product Specification		
	P/N: CPG1511F01S259	DOC. No.: KH-PS2405-37	Rev.: A Page: 2/12

Content

目录

1. Scope/范围:	3
2. Product Application/产品应用：	3
3. Technology Parameters/技术参数	3
4. Ratings/额定性能要求	3
5. Profile Dimensions /外形尺寸	3
6. Electrical Performance/电气性能	4
7. Mechanical Performance/机械性能	5~6
8. Environmental Performance/环境性能	7-9
9. Recommended PCB Layout/推荐的 PCB 安装焊盘规格	10
10. Loading Parameter Specification/荷重参数规格	11
11. Packaging/包装	11
12. Precaution/注意事项	12



凱華電子
KAIHUA ELECTRONICS

Product Specification

P/N:	DOC. No.:	Rev.:	Page:
CPG1511F01S259	KH-PS2405-37	A	3/12

1. Scope/范围:

This Product Specification covers the requirement of Mechanical Keyboard switch on product performance, test methods and quality assurance provisions.

本规格书内容涵盖机械键盘开关产品的要求，包括性能指标、测试方法及质量保证方面等。

2. Product Application/产品应用:

Mainly applied on computer keyboards, cash registers, industrial equipment and Man-Machine interface.

主要适用于电脑键盘，收银机、工业设备和人机界面。


3. Technology Parameters/技术参数

Ambient Humidity 工作湿度:	45~85% R.H.;
Operating Temperature Range 使用温度范围:	-10℃~+70℃;
Storage Temperature Range 保存温度范围:	-20℃~+70℃;
Suggested storage period 贮存期限:	about 6 months 最多 6 个月
Normal Condition:	
Ambient temperature 环境温度:	20±2℃
Relative humidity 相对湿度:	65%±5% R.H.;
Air pressure 气压:	86~108KPa;

4. Ratings/额定性能要求


Rating 额定负荷:	12V AC/DC max. 2V DC min. 10mA AC/DC max. 10 μ A DC min;
Insulation Resistance 绝缘电阻:	≥100MΩ/DC 100V;
Withstand Voltage 耐电压:	100V AC 1 Minute;
Mechanical Life 机械寿命:	50,000,000 Cycles.

5. Profile Dimensions /外形尺寸





 凱華電子 KAIHUA ELECTRONICS	Product Specification			
	P/N: CPG1511F01S259	DOC. No.: KH-PS2405-37	Rev.: A	Page: 4/12



6. Electrical Performance/电气性能

Item 项目	Description 项目描述	Test Condition 测试条件	Requirement 规格要求
6.1	Contact Resistance 接触电阻	Static load: (Operation force)x2, which is applied on the center of Switch stem. Be measured when the switch contact stabilization. 静态负载：动作力的 2 倍，施加在手柄中心。开关接触稳定时量测。 Measurement tool: Contact resistance Meter. 测量工具：微电流接触电阻计(1KHz, 20mV,5~50mA) 在低电流（≤100mA）条件下测试。 Measured at low current (100mA or less).	200mΩ Max 200mΩ 以下
6.2	Insulation Resistance 绝缘电阻	Apply a Voltage of DC 100 V for 1 minute, according to the below method. (1) Between terminals. (2) Between terminal and Body. 输入 100V DC 电压 1 分钟，按如下接触方法测试： (1) 端子与端子之间。 (2) 端子与外壳之间。	100MΩ Min 100 兆欧以上
6.3	Dielectric withstanding voltage 耐电压	Apply a Voltage of AC100 V (50~60Hz) for 1 minute, according to the below method. (1) Between terminals. (2) Between terminal and Body. 输入 100V AC 电压 1 分钟，按如下接触方法测试： (1) 端子与端子之间。 (2) 端子与外壳之间。	No evidence of breakdown 无瞬断、击穿等破坏。
6.4	Bouncing 触点抖动	Operation speed: 3~4 times/s 操作速度：每秒 3~4 次 Oscillo scope 示波器 Switch Bouncing Test Circuit 抖动测定回路。 	Before Life cycle: On:5ms MAX,5 毫秒以下 Off: 5ms MAX,5 毫秒以下 After Life cycle: On:10ms MAX,10 毫秒以下 Off: 10ms MAX,10 毫秒以下

 凱華電子 KAIHUA ELECTRONICS	Product Specification			
	P/N: CPG1511F01S259	DOC. No.: KH-PS2405-37	Rev.: A	Page: 5/12

7. Mechanical Performance/机械性能

Item 项目	Description 项目描述	Test Condition 测试条件	Requirement 规格要求
7.1	Load Curve 荷重曲线	Place the vertical direction of switch operation and gradually increase the load applied to the center of the stem until it stop. 开关的动作方向为垂直放置，向手柄中心逐渐施加负荷直到停止. 	See page 11 见第 11 页
7.2	Loading parameter 荷重参数	Place the vertical direction of switch operation and gradually increase the load applied to the center of the stem until it stop. 开关的动作方向为垂直放置，向手柄中心逐渐施加负荷直到停止. 	See page 11 见第 11 页

 		Product Specification			
		P/N:	DOC. No.:	Rev.:	Page:
		CPG1511F01S259	KH-PS2405-37	A	6/12
7.3	Static Strength 静止强度	A static load of 3kgf shall be applied in the direction of button operation for a period of 60 seconds. 在手柄动作方向施加 3kgf 的静负荷 60 秒，然后测试参数。 		No damage (Electrical) And mechanical) 电气和机械性能正常。	
7.4	Stem Pull Strength 手柄拉拔强度	Break by a pull force applied opposite to the direction of stem operation. 在推柄动作方向反向垂直施加拉力，使其破坏的程度。		5kgf Min	
7.5	Shock 机械冲击	Measured by according to the below condition: (1) Acceleration: 80g 加速度 (2) Cycles of test: 3 cycles each in 6 directions, for a total of 18 cycles. 试验次数：每个方向 3 次，6 个方向共 18 次。 		Shall meet No.6, 7.1, 7.2. 满足 6, 7.1, 7.2 要求。	
7.6	Life Test 寿命测试	1) D.C.12V 10mA resistance load D.C 12V 10mA 电阻负荷 2) Operation speed : 10 times / s 动作速度: 10 次/ 秒 3) Applying Force: 250 ± 50gf (by spring) 按力: 250±50gf 4) Operation number: 50,000,000cycles 动作次数: 50, 000, 000 次		Contact resistance: 1 Ω Max 接触电阻: 1 欧以下 Bouncing: 10ms Max 触点抖动: 10 毫秒以下 Operation force: Variation rate within ± 30% 操作力的变化范围在初始值的±30%以内。	

 凱華電子 KAIHUA ELECTRONICS	Product Specification			
	P/N: CPG1511F01S259	DOC. No.: KH-PS2405-37	Rev.: A	Page: 7/12

8. Environmental Performance/环境性能

Item 项目	Description 项目描述	Test Condition 测试条件	Requirement 规格要求												
8.1	Cold test 耐寒性	(1) Temperature : - 20±2℃ 温度： - 20±2℃ (2) Duration of test: 48h 持续时间： 48 小时 (3) Take off a drop water 去掉水珠 (4) Standard conditions after test : 1h 试验后的放置条件： 1 小时	Contact resistance: 200mΩ Max Shall meet : No. 6.2 to 6.4 No. 7.1 to 7.2 接触电阻 200mΩ 以下 满足: No. 6.2 to 6.4 No. 7.1 to 7.2												
8.2	Heat test 耐热性	(1) Temperature : 70±2℃ 温度： 70±2℃ (2) Duration of test: 48h 持续时间： 48 小时 (3) Take off a drop water 去掉水珠 (4) Standard conditions after test : 1h 试验后的放置条件： 1 小时	Contact resistance: 200mΩ Max Shall meet : No. 6.2 to 6.4 No. 7.1 to 7.2 接触电阻 200mΩ 以下 满足: No. 6.2 to 6.4 No. 7.1 to 7.2												
8.3	Temperature cycle 温度循环	(1) Test cycles: 5 cycles 试验周期： 5 个周期 (2) Standard condition after test:1h 试验后的放置条件： 1 小时 <table><tr><td></td><td>Temperature 温度</td><td>Duration of test 持续时间</td></tr><tr><td rowspan="4">1 cycle 一次循环</td><td>20±5℃</td><td>1h</td></tr><tr><td>-20±5℃</td><td>1h</td></tr><tr><td>20±5℃</td><td>1h</td></tr><tr><td>70±5℃</td><td>1h</td></tr></table>		Temperature 温度	Duration of test 持续时间	1 cycle 一次循环	20±5℃	1h	-20±5℃	1h	20±5℃	1h	70±5℃	1h	Contact resistance: 200mΩ Max Shall meet : No. 6.2 to 6.4 No. 7.1 to 7.2 接触电阻 200mΩ 以下 满足: No. 6.2 to 6.4 No. 7.1 to 7.2
	Temperature 温度	Duration of test 持续时间													
1 cycle 一次循环	20±5℃	1h													
	-20±5℃	1h													
	20±5℃	1h													
	70±5℃	1h													

 凱華電子 KAIHUA ELECTRONICS		Product Specification			
		P/N:	DOC. No.:	Rev.:	Page:
		CPG1511F01S259	KH-PS2405-37	A	8/12
8.4	Humidity test 耐湿性	(1) Temperature : 60±2℃ 温度: 60±2℃ (2) relative humidity: 90~95% R.H. 相对湿度:90~95% R.H. (3) Duration of test: 48h 持续时间: 48 小时 (4) Take off a drop water 去掉水珠 (5) Standard conditions after test: 1h 试验后的放置条件: 1 小时		Contact resistance: 200mΩ Max Shall meet : No. 6.2 to 6.4 No. 7.1 to 7.2 接触电阻 200mΩ 以下 满足: No. 6.2 to 6.4 No. 7.1 to 7.2	
8.5	Salt Spray 盐雾测试	Apply the following environment to test(Only for contact test) : 根据下列条件进行测试(仅针对触点测试): (1) Temperature : 35±5℃ 温度: 35±5℃; (2) Salt water density: 5±1% 盐水浓度: 5±1%; (3) Duration: 12hours 持续时间: 12 小时; (4) After test, the salt deposit shall be removed by running water. 实验后将盐沉积物用水冲掉		Appearance: No corrosion spot, no crack, no base plate naked. 外观: 无腐蚀点, 无裂纹, 无裸露基材. Contact Resistance: 200 mΩ Max 接触电阻: 200 毫欧以下	
8.6	Protection Against ingress of dust(IP5X) 防尘	The switches are placed in a position of normal use inside the test chamber. The test is carried out according to the second enclosure of IEC60529/GB4208. The test shall be continued for a period of 8h. 测试样品以正常使用位置在防尘箱中安装; 按 IEC60529 或 GB4208 防护标准测试条件进行试验; 试验应持续 8 小时;		After test: Operating is normal Between terminals, terminal and surface of the crust, Dielectric withstand in voltage ≥100V 动作正常; 端子之间及端子与外壳表面耐电压强度≥100V	

 			Product Specification			
			P/N:	DOC. No.:	Rev.:	Page:
			CPG1511F01S259	KH-PS2405-37	A	9/12
8.7	Protection against ingress of water(IPX4) 防水	The switches are placed in a position of normal use inside the test table. The test is carried out according to the second enclosure of IEC60529/GB4208. 测试样品以正常使用位置在防水箱中安装； 按 IEC60529 或 GB4208 防护标准测试条件进行试验；		After test: Operating is normal. Water don't enter electric parts of the switch inside. Between terminals, terminal and surface of the crust, Dielectric withstand in voltage $\geq 100V$ 动作正常； 水不能进入开关内带电部份 端子之间及端子与外壳表面耐电压强度$\geq 100V$		




凱華電子
KAIHUA ELECTRONICS

Product Specification


P/N: CPG1511F01S259	DOC. No.: KH-PS2405-37	Rev.: A	Page: 10/12
------------------------	---------------------------	------------	----------------

9. Recommended PCB Layout 推荐的 PCB 安装焊盘规格

Mounting Options 安装选项



PCB (with pins)



Metal Frame (without pins)

10. Loading Parameter (TT/PT/OT /OF) Specification 荷重参数规格：

Parameter	Unit	Specification	Remark
TT(总行程)	mm	3.6 + 0.3/-0.2	
TF（触感力）	gf	60±10	
PT(导通行程)	mm	1.8±0.4	
OT(过行程)	mm	1.2	Min.
OF(操作力)	gf	50±15	
RF（回弹力）	gf	15	Min.

11. Packaging 包装

Packaging type: Tray, 1000Pcs/Tray, 4000Pcs/Carton.

包装方式: Tray 盘,1000Pcs/盘, 4000Pcs/箱.



 凱華電子 KAIHUA ELECTRONICS		Product Specification			
		P/N: CPG1511F01S259	DOC. No.: KH-PS2405-37	Rev.: A	Page: 12/12
12.Precaution 注意事项 (1) Please be cautious not to give excessive static load or shock to switches. 注意不要施加超负荷的压力或晃动开关. (2) Preservation under high temperature and high humidity or corrosive gas should be avoided Especially. When you need to preserve for a long period, do not open the carton. 保管时尤其应注意避开高湿高温和有腐蚀性气体的环境.如需长时间保存,请不要打开包装箱. (3) The standard storage period is 3 months, with maximum up to 6months, preferably to be used as soon as possible. After opening the package, you should put the remaining switches in a plastic bag to prevent from damp and corrosive gas. 保存标准为 3 个月，限度为 6 个月以内，请尽早使用. 打开包装后，有剩余品时，应将剩余部分以胶袋包装好以同外界隔离，请进行合适的防湿，防腐蚀气体等处理后进行保管. (4) This Product Specification is considered as the technical agreement on product between the receiving customer and Kailh. Any information on Product Catalogue which is in conflict with or different from the corresponding information of this document is considered as invalid. 该规格书为客户与凯华公司产品在技术方面的共识，其他相关数据上与该规格书不一致的内容都是无效的. (5) It will be considered that customer already confirmed and accepted this specification if customer issue purchase order to us directly. 无论顾客收到规格书后有没有信息反馈直接向我公司订货，我们将认为顾客对此产品已验证合格. (6) If there is no order or no request for new specification after 1 year upon this specification is issued, the specification will be regarded as invalid. 本产品规格书从生效日起 1 年后，如果没有订货或再次申请最新规格书时请做无效处理. (7) Products meet the ROHS & REACH environmental management substances control standards 产品满足 ROHS & REACH 环境管理物质管制标准					