

Product Name	RJ45 Connector, CAT6 Shielded for CAT6 FTP 2+6, 100mΩ Insulation Resistance
Model No	C6R5Z50VSIL with insert (2+6)
Origin	Ningbo, China
Brand Name	EXW or OEM case.
Packing	100pcs/bag, 5000pcs/inner box, 2 inner boxes / carton.
Unit price	0.1~0.2 USD/pcs.
Delivery Time	3~4 weeks, urgent order: within 2 weeks.
MOQ	5,000pcs
Capability	600,000pcs/day
Certificate	ISO9001:2001 / ISO14001 / OHSAS18001 / UL / RoHS / REACH.

Product Description:

1.Product Name: RJ45 Connector, CAT6 Shielded for CAT6 FTP 2+6, 100mΩ Insulation Resistance

2.Suitable for cable: round, both solid and stranded cable 24/26AWG;

3.Contact blade: Copper Alloy with gold plating 50u, the standard gold thickness 03U, 06u, 15u, 30u, 50u could be optional.

4.Housing Material: Japan Teijin PC, UL 94-V2, UL 94-V0 is available.

5.Shielded Shell: Copper Alloy.

6.Color: Transparent, or with Transparent color, or not transparent, 3 options.

7.Mechanical: Fully comply with FCC standard.

7.1 Cable to plug strength 25 POUND MIN.

7.2 Durability: mating cycle 750 operations.

8. Electrical:

UL Applications: 250 VOLTS AC MAX, AT 2 AMPS.

Dielectric Withstanding voltage: 500 VOLTS AC.

Insulation Resistance: 100MΩ

Termination test: Resistance 20mΩ max after environmental testing.

9. Packing rate:

SPEC.	Q'TY PCS/CTN	N.W. KGS	G.W. KGS	Dimension(cm)
6P2C	20,000	15.96	17.50	49.6*36.2*26.5
6P4C	20,000	15.86	17.40	49.6*36.2*26.5
6P6C	20,000	16.13	18.03	49.6*36.2*26.5
4P4C	25,000	16.59	18.23	49.6*36.2*26.5
8P8C	10,000	15.26	17.00	49.6*36.2*26.5
8P Shielded	10,000	25.40	27.50	51.6*36.2*32.0
Cat.6 UTP	10,000	13.70	15.80	51.6*36.2*32.0
Cat.6 Shielded	10,000	23.72	25.82	51.6*36.2*32.0

10. Packing picture: 1000pcs/bag, or 100PCS/bag is optional;



11. Quality Control: AOI system (Automatic Optical Inspection);

