

DAEWOO

15" Color Monitor

CMC-532X



SPECIFICATIONS

CRT	Size	15" Diagonal(FST)
	Viewable Size	14.1"
	Dot Pitch	0.28mm
	Phosphor	RGB medium-short persistence
Scanning Frequency	Horizontal	30 ~ 54KHz
	Vertical	50 ~ 160Hz
Bandwidth		80MHz
Resolution	Maximum	1024 x 768 @ 60Hz
	Recommended	800 x 600 @ 85Hz
Display Area	Normal	264mm(H) x 198mm(V)
	Maximum	266mm(H) x 216mm(V)
Input Signal	Video	RGB Analog (0.7V/1.0V p-p, 75ohms)
	Sync	H/V Separate (TTL)
Input Signal Connector		15pin D-Sub
Plug & Play		DDC 1/2B/C/D
USB (optional)	Stand Based-on Hub	1 upstream, 4 downstream
User Control Buttons		Power on/off, Menu, up, down, left, right
On Screen Display Control	Hot Key Control	Contrast, Brightness
	Size Position	H-Size, V-Size, H-Position, V-Position, V-Linearity
	Geometry	Pincushion, Trapezoid, Pin-Balance, Parallelogram, Top Pin-Corner, Bottom-Corner
	Color	Color Temperature (5300°K/6500°K/User), R-Gain, G-Gain, B-Gain, R-Bias, G-Bias, B-Bias
	Language	5 Languages (Eng, Ger, Esp, Fra, Ital)
Power Voltage	Utility	Degauss, Status, Recall
		AC 100 ~ 240V @ 60/50Hz, Universal Power
Power Saving	On	70 Watt
	Suspend/Stand-by	15 Watt
	Off	5 Watt
Dimension (with Stand)	W x H x D	360mm x 377mm x 389mm
Weight	Net	11.5K g
	Gross	13.1K g
Regulation	Low Radiation	MPR II
	Safety & Ergonomics	UL, CSA, CHHS, GS, EMKO, PCBC, ISO-9241 partB
	EMC (EMI/EMS)	FCC-B, CE, C-Tick, VCCI (optional)
Power Management		EPA Energy Star, VESA DPMs Compliant
Environmental Conditions	Operating	Temperature : 10 to 40°C Humidity : 8 to 80% (non-condensing)
	Storage	Temperature : -20 to 45°C Humidity : 5 to 90% (non-condensing)

