



4G LTE portableUFI
Model: EP-N9518

Description

Hardware information		Cat4	Remarks
The processor	ZTE7520		
spectrum	FDD LTE B1/B3/B5/B8/B7 TDD LTE B38/B39/B40/B41 TD-SCDMA B34/B39 WCDMA B1/B5/B8		B4/B7/B20/B28ab
Peak rate	LTE download : 150Mbps, upload : 50Mbps (Category 4)		USB Interface/SIM Card slot 2 in1
The keys	The power button Restore the factory button (pinhole)		
WIFI	Support 802.11 b/g/n		
interface	MicroUSB interface Standard USIM interface MicroSD interface		
The antenna	built-in		
The adapter	The input voltage : 100V~240V,50Hz~60Hz		

	The output voltage : 5V DC±10% The output current : 1A	
Charging interface	Micro 5pin	
Working temperature	-10°C to 60°C	
Working humidity	10% - 95%	
Storage temperature	-40°C to 85°C	
Store humidity	5% to 95%	
Software information		
The operating system	Win7, Windows XP, Vista, Mac OS	
language	Chinese/English	Support multiple languages
Shared)	Up to 10 users	
Set up the)	support	
SMS	Support mobile and Unicom conventional card receiving and sending, telecommunication cards do not support	
The phone book	support	
APN Settings	support	
WIFI Settings	support	
Device Settings	support	
Routing setting	support	
Firewall Settings	support	
certification		
		Meet customer requirements
Other information		
size	59x98x15.5 mm	98mmX58.5mmX15mm (For reference only)
The weight of the	86.04g	
The standby time	Can reach more than 50 hours	Ultimately decided by the battery
Work hours	Can reach more than 6 hours (Only connect to one device)	Ultimately decided by the battery