

Industrial Computers

- ARM series
- VOPC ratio screens

Key Series Features

- 15", 17" and 19" True Flat Touch Screens
- ARM, Rockchip
- Fanless Operating System
- Wide Range Power Input
- Steel Chassis Housing, IP65 Rated Front Panel



SKU	VOPC-15	VOPC-17	VOPC-19
Screen Size	15"	17"	19"
Resolution	1024x768	1280x1024	1280x1024
Viewing Angle	89/89/89/89	85/85/80/80	85/85/80/80
Brightness	350 cd/m²	250 cd/m²	250 cd/m²
Contrast Ratio	1000:1	1000:1	1000:1
Touchscreen	Capacitive		
Controller	USB interface		
Durability	≥ 5M times		
Processor Family	ARM, Rockchip		
Memory Type	2G, 4G, 8G		
Storage Type	32G, 64G, 128G	3588: 64G, 128G, 256G	
Ethernet / LAN	1x LAN	2 x LAN	
Serial / Com	2x RS232 (1x COM option RS485)		
USB	2 x USB		
Video Outputs	1x HDMI		
Expansion Slots	1x Mini PCIE		
Operating Systems	Android, Linux		
Dimension	358.4x286.7x49.5mm	384.1x316.2 x50.7mm	429x356.5x49.2mm
Mounting Hole Size	349.4 x277.2mm	381x312.9mm	425.5x350.5mm
Gross Weight	3.70kg	5.60kg	6.20kg
Mounting Options	Embedded, Wall Mount, Desktop Stand		
Operating Temperature	-30 C ~ +70 C		
Storage Temperature	-40 C ~ +80 C		
Humidity Rage Non-condensing	5% - 95%		
Power	Input Voltage Range 9 – 36V DC Standard Power: Optional 12V AC/DC Adapter: 5A, 60W		

- ARM series
- VOPC wide screens

Key Series Features

- 15.6" to 32" True Flat Panel Touch Screens
- ARM, Rockchip Processors
- Fanless Operating System
- Wide Range Power Input
- Steel Chassis Housing, IP65 Rated Front Panel



SKU	VOPC-156	VOPC-185	VOPC-215	VOPC-236	VOPC-27	VOPC-32
Screen Size	15.6"	18.5"	21.5"	23.6"	27"	32"
Resolution	1366 x768	1920 x1080	1920 x1080	1920 x1080	1920 x1080	1920 x1080
Viewing Angle	45/45/20/40	89/89/89/89	89/89/89/89	89/89/89/89	89/89/89/89	89/89/89/89
Brightness	220 cd/m²	250 cd/m²	250 cd/m²	250 cd/m²	250 cd/m²	250 cd/m²
Contrast Ratio	500:1	1000:1	3000:1	3000:1	1000:1	1200:1
Touchscreen	Capacitive					
Controller	USB interface					
Durability	≥ 5M times					
Processor Family	ARM, Rockchip					
Memory Type	2G, 4G, 8G					
Ethernet / LAN	1x LAN			2 x LAN		
Serial / Com	2x RS232 (1x COM option RS485)					
USB	2 x USB					
Video Outputs	1x HDMI					
Expansion Slots	1x Mini PCIE					
Operating Systems	Android, Linux					
Dimension	392 x 242 x 49.5mm	457.2x281.7x49.6mm	533.6x320.9x51.3mm	572.1x345.6x51.3mm	657x398x51.5mm	770.7x465.6 x57.2mm
Mounting Hole Size	387.2 x 237.2mm	453.4x277.5mm	527.9x314.9mm	567.6x341.2mm	651.1x394.2mm	765.6x460.3mm
Gross Weight	3.70kg	4.10kg	5.70kg	6.00kg	9.20kg	12.50kg
Mounting Options	Embedded, Wall Mount, Desktop Stand					
Operating Temperature	-30℃ ~ +70℃					
Storage Temperature	-40℃ ~ +80℃					
Humidity Rage Non-condensing	5% - 95%					
Power	Input Voltage Range 9 – 36V DC Standard Power: Optional 12V AC/DC Adapter: 5A, 60W					

All specifications are subject to change without notice. For more information and please contact our sales team.