

Product description

Solid or stranded ,tinned or bare copper conductor 40AWG min

PVC insulation ,comply with ROHS environmental standard

Tinned or bare copper wire braid shield

PVC jacket , comply with ROHS environmental standard

Uniform insulation thickness to ensure easy stripping and cutting

Rated temperature: 80°C

Rated voltage: 30V

Reference standard: UL758,UL1581,CSA C22.2No.210.2

Type: Multi core Low Voltage Computer Cable

Material: Copper conductor, PVC insulation, Tinned or bare copper, PVC jacket

Flame retardant grade: UL VW-1 and JQA -F-Mark flame test

STYLE	CORE		CONDUCTOR		INSULATI	SHIELD	JACKET	JACKET
					O.D.		THICKNES	O.D.
	(No.)	STYLE	AWG	CONSTRU CTION (No./mm)	(mm)		(mm)	(mm)
1+4	1	1792	28	7/0.127	2.4	AL-MYLAR	0.84	6.1
	4	1061	24	7/0.20	1.1	+DRAIN		
1+8	1	1792	28	7/0.127	2.4	+BRAID	0.85	6.8
	8	1061	24	7/0.20	1.1			
3+4	3	1792	28	7/0.127	2.4		0.83	7.5
	4	1061	24	7/0.20	1.1			
3+5	3	1792	28	7/0.127	2.4		0.83	7.7
	5	1061	24	7/0.20	1.1			
3+6	3	1792	28	7/0.127	2.4		0.84	8.1