



ORANGE LIGHTING (DONGGUAN) CO., LTD

BO YA LIGHTING (HK) CO., LTD

Factory: 3rd Floor, H Elevator, Building C, No. 39 YI HUI 1st Road, Heng Lan Town, Zhongshan City, Guangdong, China (ZS)
 4/F, No. 27 Zhenchang Road, Guancang Management Area, Zhangmutou Town, Dongguan, Guangdong, China. 523629 (DG)
 Tel: +86-0769-33539892 Fax: +86-0769-82051860 Web: www.lightinggreen.cn

Datasheet for slim Led Panel Light

NO.	Model	Picture	Dimension	Input Voltage (V)	CRI	CCT(K) (optional)	Emitting Angel (°)	Power (W)	Flux(LM)	Warranty
1	BY-RPD-3C (2.5")		Dimension: Ø85*H9mm Cut-out Size: Ø70mm	AC110-240V	>80Ra	6000-6500K 4000-4500K 2800-3500K	>120°	3w	100LM/W	2 years
2	BY-RPD-6C (3.5")		Dimension: Ø120*H9mm Cut-out Size: Ø105mm	AC110-240V	>80Ra	6000-6500K 4000-4500K 2800-3500K	>120°	6w	100LM/W	2 years
3	BY-RPD-9C (4")		Dimension: Ø150*H9mm Cut-out Size: Ø120mm	AC110-240V	>80Ra	6000-6500K 4000-4500K 2800-3500K	>120°	9w	100LM/W	2 years
4	BY-RPD-12C (5")		Dimension: Ø170*H9mm Cut-out Size: Ø150mm	AC110-240V	>80Ra	6000-6500K 4000-4500K 2800-3500K	>120°	12W	100LM/W	2 years
5	BY-RPD-15C (6")		Dimension: Ø200*H9mm Cut-out Size: Ø170mm	AC110-240V	>80Ra	6000-6500K 4000-4500K 2800-3500K	>120°	15W	100LM/W	2 years
6	BY-RPD-18C (8")		Dimension: Ø225*H9mm Cut-out Size: Ø205mm	AC110-240V	>80Ra	6000-6500K 4000-4500K 2800-3500K	>120°	18W	100LM/W	2 years
7	BY-RPD-24C (10")		Dimension: Ø300*H9mm Cut-out Size: Ø275mm	AC110-240V	>80Ra	6000-6500K 4000-4500K 2800-3500K	>120°	24W	100LM/W	2 years

1	BY-FPD-3C (2.5")		Dimension:L85*W85*H9mm Cut-out Size:L70*W70mm	AC110-240V	>80Ra	6000-6500K 4000-4500K 2800-3500K	>120°	3w	100LM/W	2 years
2	BY-FPD-6C (3.5")		Dimension:L120*W120*H9mm Cut-out Size:L105*W105mm	AC110-240V	>80Ra	6000-6500K 4000-4500K 2800-3500K	>120°	6w	100LM/W	2 years
3	BY-FPD-9C (4")		Dimension:L150*W150*H9mm Cut-out Size:L120*W120mm	AC110-240V	>80Ra	6000-6500K 4000-4500K 2800-3500K	>120°	9w	100LM/W	2 years
4	BY-FPD-12C (5")		Dimension:L170*W170*H9mm Cut-out Size:L155*W155mm	AC110-240V	>80Ra	6000-6500K 4000-4500K 2800-3500K	>120°	12W	100LM/W	2 years
5	BY-FPD-15C (6")		Dimension:L200*W200*H9mm Cut-out Size:L175*W175mm	AC110-240V	>80Ra	6000-6500K 4000-4500K 2800-3500K	>120°	15W	100LM/W	2 years
6	BY-FPD-18C (8")		Dimension:L225*W225*H9mm Cut-out Size:L205*W205mm	AC110-240V	>80Ra	6000-6500K 4000-4500K 2800-3500K	>120°	18W	100LM/W	2 years
7	BY-FPD-24C (10")		Dimension:L300*W300*H9mm Cut-out Size:L275*W275mm	AC110-240V	>80Ra	6000-6500K 4000-4500K 2800-3500K	>120°	24W	100LM/W	2 years
1	BY-R(S)PD-6C		Dimension:Ø120*H32mm	AC110-240V	>80Ra	6000-6500K 4000-4500K 2800-3500K	>120°	6w	100LM/W	2 years
2	BY-R(S)PD-12C		Dimension:Ø170*H32mm	AC110-240V	>80Ra	6000-6500K 4000-4500K 2800-3500K	>120°	12W	100LM/W	2 years
3	BY-R(S)PD-18C		Dimentions:Ø225*H32mm	AC110-240V	>80Ra	6000-6500K 4000-4500K 2800-3500K	>120°	18W	100LM/W	2 years
4	BY-R(S)PD-24C		Dimension:Ø300*H32mm	AC110-240V	>80Ra	6000-6500K 4000-4500K 2800-3500K	>120°	24W	100LM/W	2 years
1	BY-SLS-6C (4")		Dimension:L120*W120*H32mm	AC110-240V	>80Ra	6000-6500K 4000-4500K 2800-3500K	>120°	6w	100LM/W	2 years

2	BY-SLS-12C (5")		Dimension:L170*W170*H32 mm	AC110-240V	>80Ra	6000-6500K 4000-4500K 2800-3500K	>120°	12W	100LM/W	2 years
3	BY-SLS-18C (8")		Dimension:L225*W225*H32 mm	AC110-240V	>80Ra	6000-6500K 4000-4500K 2800-3500K	>120°	18W	100LM/W	2 years
4	BY-SLS-24C (10")		Dimension:L300*W300*H32 mm	AC110-240V	>80Ra	6000-6500K 4000-4500K 2800-3500K	>120°	24W	100LM/W	2 years