



## 58MM Portable Thermal Printer HCC-T2P

### Features

- Mini size, Light weight, Durable performance
- 1500mAH, 7.4V rechargeable lithium battery, quick charge
- Continuously work for 6 hours or 200km
- 80mm/s high printing speed
- Support various languages, easy to use
- Standard interface: USB(Virtual Serial), Bluetooth, WIFI (Apple and Android)
- Support Dots Printing With different densities
- Support raster Bitmap Print
- Support 2D and 1D QR CODE Printing
- Support OEM/ODM.
- Support Windows (Win10/ WIN7/WIN8/Vista/XP/2000)
- Ubuntu 12.04 32/64, Ubuntu 14.04 32/64 drivers.
- Wonderful SDK templates For Linux(C++),Windows,Android, IOS

### Specification

|               |                          |  |
|---------------|--------------------------|--|
| Print         | Printing Method          | Thermal Line   |
|               | Printing Speed           | 50-80mm/s  |
|               | Resolution               | 8 dots/mm, 384 dots/line   |
|               | Effective Printing Width | 48mm   |
| Communication | Wired                    | Standard: Mini-USB Port, Optional: Serial Port(PS/2)   |
|               | Wireless                 | Bluetooth  |
| Character     | Character Set            | ASCII9*17,12*24, GB2312-80(Chinese)  |
|               | Print Font               | ANK:(8x16,9x17,9x24,12x24) , GBK: 16x16, 24x24   |
|               | Language(Code Page)      | Support Simplified & Traditional Chinese, English and other 45 kinds of International Character Sets |
| Paper Spec    | Paper Type               | Thermal paper  |
|               | Paper Width              | 57.5± 0.5mm  |
|               | Paper Roll Diameter      | Max: 40mm  |
| Software      | Drivers                  | Windows(win10/ win8/win7/vista/xp/2000);   |

|                                |                    |  |
|--------------------------------|--------------------|--|
|                                |                    | Ubuntu 12.04 32/64 Ubuntu 12.04 32/64 Ubuntu 14.04 32/64   |
|                                | App                | Printer setting tools  |
| Barcode                        | 1D                 | UPC-A, UPC-E, EAN-8, EAN13, CODE39, ITF, CODEBAR, CODE128 Etc..  |
|                                | 2D                 | QR Code  |
| Indicators LED                 |                    | Power(red), Battery Charging(Green), Bluetooth and out of paper(Blue)  |
| Paper tore                     |                    | Manual   |
| Detection Sensor               |                    | Out of Paper   |
| Battery                        |                    | Rechargeable Li-ion Battery, 7.4V, 1500mAh   |
| Charger Power Supply (Adapter) |                    | Input: 100-240VAC/0.5A, 50/60Hz; Out Put: 12V DC/1A  |
| Dimension                      |                    | L*W*H: 12*7.4*4.4cm  |
| Environment                    | Operating Temp     | 5°C ~ 50°C   |
|                                | Operating Humidity | 10% ~ 80%  |
|                                | Storage Temp       | -20°C ~ 60°C   |
|                                | Storage Humidity   | 10% ~ 90%  |
| Accessory                      |                    | 1* User Manual,<br>1* CD Driver,<br>1* Power Adapter<br>1*USB Data Cable<br>1*Test Paper Rolls<br>1*battery                    |
| Packing                        |                    | One set size: 180*125*65mm;<br>One set Weight: 0.4kg;<br>25pcs per carton;<br>Carton size: 61*34*21cm;<br>Carton weight: 12kg. |

### Application

- Supermarket
- Catering
- Store
- Tax
- Bank
- Medical Care
- Storage
- Post



Picture

