

Technical Specifications

技术参数

Product / 产品	KJ-302A DTF PRINTER / KJ-302A 白墨烫画机		
Model / 型号	KJ-302A		
Printhead / 喷头	2*Epson i3200A1	2*Epson i1600A1	2*Epson xp600
Printing Speed / 打印速度	4 Pass: 12sqm/h 6 Pass: 9sqm/h	4 Pass: 6sqm/h 6 Pass: 5sqm/h	4 Pass: 5sqm/h 6 Pass: 4sqm/h
Color / 墨水颜色	5 colors 5 色 (C, M, Y, K, W)		
Max Media Width / 进料最大宽幅	430mm		
Max Print Width / 打印最大宽幅	420mm		
Ink Type / 墨水类型	Waterbased Pigment Ink 水性颜料墨水		
Media Type / 介质类型	PET film PET 膜		
Heating System / 加热系统	Intelligent Embedded Heating System 嵌入式智能加热系统 Powder Melt Machine 抖粉加热系统		
Feed & Take up System / 收放布系统	Equipped 配备		
Ink System / 供墨系统	Automatic ink supply white ink circulating and stirring 自动彩墨供墨系统 + 白墨循环系统		
Clamp / 防翘压片	Combined Anti-warping Clamps 组合式匀阻力防翘压片		
Power Electric Supply / 电压	110V/220V 50-60HZ		
Power / 功率	350W-3400W		
RIP Software / RIP 软件	Maintop, Photoprint, CADlink (Optional)		
Working Environment / 使用环境	Temperature 温度 : 18-32°C Humidity 湿度 : 46-65%		
Printer size / 打印机尺寸	1100*510*625mm 70KG		
Shacker size / 抖粉机尺寸	800*510*510mm 50KG		
Packing Size / 包装尺寸	Printer打印:1320*730*850mm; 105.5KG; 0.819CBM Shaker抖粉:1080*880*730mm; 94KG; 0.700CBM		