

Specification	
Model:	C6S2X-H
APP:	V380 Pro
System structure:	Embedded Linux system, ARM chip
Chip:	AK3918E V330L
Resolution:	3.0MP
Sensor Resolution:	1/2.9"SC2336 2304*1296
Lens	4MM
View angle:	80°
Pan-tilt:	Rotates Horizontal:355° Vertical: 90°
Preset point quantity:	6
Video compression	H.265/20FPS
Video format:	PAL
Minimum illumination:	0.01Lux@ (F2.0, VGC ON),0.Luxwith IR
Electronic shutter:	Auto
Backlight	Support
Noise reduction:	2D、3D
Led quantity:	4pcs White Led + 4pcs Infrared LED
Connection method:	WIFI, AP hotspot , RJ45 Network port
Network:	WIFI wireless transmission (support
Night vision	IR-CUT switch Automatic, about 5-8meters (It varies from environment)
	White Led can be remote control via APP: ①Turn ON ②Turn OFF ③ Auto
	(In automatic mode, the infrared light will be turned ON after the IR-cut switch to night vision automatically , it can
	intelligently detected human body, and Turn ON/OFF the White light intelligently)
Audio:	Built-in microphone and speaker, support two-way audio and real-time transmission.
	ADPCM audio compression standard, self-adapt to code stream
Network protocol:	TCP/IP、DHCP
Alarm:	①Motion detection and picture push ②AI Human intrusion Detection (optional)
Storage:	TF Card (Max 128G) ; Cloud storage /Cloud disk (optional)
Power input:	12V/2A
Work environment:	Working temperature:-10℃ ~ + 50℃ Working Humidity: ≤95%RH

Work environment:	Working temperature:-10℃ ~ + 50℃ Working Humidity: ≤95%RH
-------------------	--