




Haresan Standard PMOLED Display List

Shenzhen Haresan Electronics Co.Ltd Yolanda Duan Email: Yolanda@hesoled.com
Mob:+86-18926513667 Skype:Ledyolanda Website:www.hesoled.com

Size (inches)	Part Number	Resolution/ Color	Interface	Controller	Dimensions(mm)	Active Area(mm)
0.42"	HEM-P7240-001B	72× 40 (White)	4-SPI/IIC	SSD1306BZ	12 × 11 × 1.2	9.2×5.18
0.49"	OHEM6432-03	64 × 32 (White)	I ² C	SSD1306	14.5 × 11.6 × 1.2	11.18 × 5.58
0.66"	OHEM6448-01	64 × 48 (White)	SPI,I2C,68/80XX	SSD1306	18.46 × 18.1 × 1.25	13.42 × 10.06
0.66"	HP6448-TSWG28	64 × 48 (White)	6800/8080, 4 wire serial, I2C	SSD1306BZ	18.46x18.1x1.21	13.42 x10.06
0.69"	OHEM9616-01	96 ×16(White)	I2C	SSD1306	26.3x8x1.2	17.26x3.18
0.87"	HEM-P12832-002A	128x32 (White)	I2C	SSD1316Z	29.0x8.7x1.22	21.356 x5.324
0.91"	OHEM12832-09	128x32 (White)	I ² C	SH1106G	40.5×11.5×1.28	22.38 ×5.58
0.96"	OHEM12864-03	128×64 (White)	8-bit 68XX/80XX Parallel, 3/4wire SPI, I2C	SSD1306	26.70 × 19.26 × 1.4	21.744 × 10.864
0.96"	HP12864-37-KSWG30P096-A	128×64 (White)	6800/8080 interface, 4 wire serial interface, I2C	SSD1306BZ	26.7x19.26x1.41	21.744 x10.864
0.96"	OHEM12864-13B	128×64 (White)	3/4 wire Serial Peripheral , I2C	SSD1315Z	24.74x16.9x1.42	21.74 × 10.86
0.96"	OHEM12864-03C	128×64(Blue)	4 Wire SPI	SSD1306	26.70 × 19.26 x1.5	21.744 × 10.864
0.96"	P12864-006A	128X64Blue & Yellow	Parallel/Serial/IIC	SSD1306BZ	26.70 × 19.26	21.74 × 11.20
1.1"	OHEM9696-01	96x96 262K/65K	8/16-bit 8080-series Parallel Interface,SPI	SSD1351	25.8 × 48.1 × 1.227	20.135 × 20.14
1.12"	OHEM9696-03	96x96 (White)	8-bit 8080-series Parallel Interface,SPI, I2C	SSD1327	27 × 42.11 × 1.61	20.14 × 20.14
1.1"	OHEM9664-01	96x64 (Yellow)	8-bit 6800/8080 series parallel interface,SPI	SSD1325	29 × 67.7 × 2.41	23.49 × 15.65
1.3"	OHEM12864-05	128x 64 (White)	8-bit 68XX/80XX Parallel, 4-wire SPI, I2C	SH1106G	34.5 × 23.0 × 1.4	29.42x 14.7
1.3"	HEM1286401W30P130-A0	128x 64 (White)	6800/8080/3-SPI /4-SPI / I2C	SH1116G	34.50 × 23.00 × 1.26	29.42 × 14.20
1.3"	OHEM160160-02B	160x 160(White)	Serial Peripheral Interface	SSD1319Z	26.74x30.0x1.23	23.34x 23.34
1.5"	OHEM128128-01	128x 128 (White)	8-bit 68XX/80XX Parallel, SPI, I2C	SSD1327	33.8 ×43.7 ×1.41	26.86 ×26.86
1.54"	OHEM12864-11B	128 × 64 (Blue)	8080-series parallel interface, SPI, I2C	SPD0301	42.04 × 63.22 × 1.41	35.052 × 17.516
1.54"	P12864-005A	128×64 (White)	8080-series parallel interface, SPI, I2C	SPD0301	42.04 × 27.22 × 1.4	35.052 × 17.516
1.54"	P12864-009A	128×64 (White)	Parallel / SPI/ IIC	SSD1309Z	42.04 × 27.22 × 1.45	35.04 × 17.51
1.6"	OHEM12864-17	128 × 64 (Yellow)	8-bit 8080-senres parallel interface, SPI	SSD1325	41.9 × 65.751 × 2.41	36.45 × 18.21
1.8"	OHEM25632-01	256× 32 (White)	8-bit 68XX/80XX Parallel, SPI, I2C	SSD1326	52 × 34.7 × 1.81	46.06 × 5.74
2.4"	OHEM12864-09	128 × 64 (Yellow)	8-bit 68XX/80XX Parallel, SPI, I2C	SPD0301	60.5 × 47 × 2.027	55.01 × 27.49
2.42"	OHEM12864-24	128 × 64 (White)	Parallel / Serial/IIC	SSD1309ZC	60.5 × 37.00	55.01 × 27.49
3.2"	OHEM25664-01	256 × 64 (White)	Parallel, SPI	SSD1322U1R1	87.4×28.5×2.01	79.084×19.756

Update time: 2022/2/20



Yolanda Duan
Overseas Project Manager



Shenzhen Haresan Electronics Co., Limited

Office Address: 16&2th Floors Building B, YADIBAO industria Area,
No.5 of Huating road,Dalang Street,Longhua, Shenzhen, China
Factory Address: The Huaersheng Industrial Area of Wanzai
New&High-tech Industrial Park, Yichun city, Jiangxi province.
Tel: +86-755-28033960 Fax: +86-755-28033850
Mobile phone:+86 189 2651 3667 E-mail:yolanda@hesoled.com
skype:Ledyolanda Http: www.hesoled.com
Specialize in making the best OLED and LCD display in China