

## Portable Thermal Printer HCC-A4PP

### Specification

|                        |                                                                                                                          |
|------------------------|--------------------------------------------------------------------------------------------------------------------------|
| Printing Method        | Thermal line printing                                                                                                    |
| Effective Width        | 210mm/216mm                                                                                                              |
| Print Instructions     | ESC                                                                                                                      |
| Printing Speed         | Maximum printing speed is 30mm/s                                                                                         |
| Print Density          | 8 dots/mm (203dpi), 1728 dots/line                                                                                       |
| Character Size         | 12*24, 24*24                                                                                                             |
| Connection Method      | Android & iOS & Windows                                                                                                  |
| Print Interface        | USB + Bluetooth                                                                                                          |
| Bluetooth Version      | 4.0 / (above 4.0)                                                                                                        |
| Software Function      | Edit notes, take photos to search for questions, text recognition, print templates, document printing, web page printing |
| Maximum Paper Width    | 216±1mm                                                                                                                  |
| Support Paper          | Thermal receipt paper                                                                                                    |
| Diameter Of PaperBbin  | The maximum outer diameter that can be used is φ30mm                                                                     |
| Paper Thickness        | 0.05-0.15mm                                                                                                              |
| Paper Loading Method   | Easy paper loading structure                                                                                             |
| Targeting              | Photoelectric sensor                                                                                                     |
| Status Display         | Power on, out of paper, charging, Bluetooth (LED indicator)                                                              |
| Standby Time           | 3 days                                                                                                                   |
| Print Head Life        | 50KM                                                                                                                     |
| Full Power Printing    | 50m                                                                                                                      |
| Charging Time          | 4 hours                                                                                                                  |
| Out Of Paper Detection | Optocoupler detection                                                                                                    |
| Lithium Battery        | 2500mAh high performance polymer                                                                                         |
| USB Type               | Type-C                                                                                                                   |
| Adapter                | DC 15V / 1A                                                                                                              |
| Size                   | 267*95*51*mm                                                                                                             |
| Weight                 | 1350g                                                                                                                    |
| Working Environment    | Temperature: 0-45℃                                                                                                       |
|                        | Humidity: 20-90%                                                                                                         |
| Storage Environment    | Temperature: -10-60℃                                                                                                     |
|                        | Humidity: 10-90% (except paper rolls)                                                                                    |

### Picture

