

HSPOS TECHNOLOGY LIMITED

5 floor, A1 building, Nanshui industrial
park, Sanjiao Town, Zhongshan City, Guangdong Province, China

Tel+86 0760-85546950 Fax+86 0760-85546950

Website: www.hsprinter.com

Email: info@hsprinter.com



HS-802-UE Series Thermal Receipt Printer with cutter

Function

- Item Name: Thermal Receipt Printer
- Suitable for all types of commercial retail POS systems
- Light in weight and smart in shape
- High-quality printing and low cost
- Support cash drawer driver
- Compatible with Uber eat and foodpanda
- Support auto cutter paper
- Easy for paper installation, Easy maintenance and excellent structure
- Low power consumption and low operating costs (No Ribbons or Ink)
- Fashionable design, Splendid quality
- High-speed printing, High performance
- Support Logo download and print
- International language
- support USB, serial, Parallel, LAN, Bluetooth interface(optional)
- Support Windows (Win10/ WIN7/WIN8/Vista/XP/2000) Ubuntu 12.04 32/64, Ubuntu 14.04 32/64



Application



Supermarket



Catering



Store



Tax



Bank



Medical care



Storage



Post



Parameters

Printing method	Direct thermal
Print width	72mm
Column capacity	384 dots/line
Printing speed	180mm/s
Interface	USB+Bluetooth+wifi
Printing paper	79.5±0.5mm × φ 60mm
Line spacing	3.75mm (Adjustable by commands)
Column number	80mm paper: Font A - 32 columns/Font B - 42 columns/ Chinese, traditional Chinese - 16 columns
Character size	ANK, Font A: 1.5×3.0mm (12×24 dots) Font B: 1.1×2.1mm (9×17 dots) Chinese, traditional Chinese: 3.0×3.0mm (24×24 dots)
Barcode Character	
Extension character sheet	PC347 (Standard Europe)、Katakana、PC850 (Multilingual)、PC860 (Portuguese)、PC863 (Canadian-French)、PC865 (Nordic)、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2)、PC852 (Latin2)、PC858、IranII、Latvian、Arabic、PT151 (1251) etc.... 26 languages
Barcode types	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) / CODE39/ITF/CODABAR/CODE93/CODE128
Buffer	
Input buffer	32k bytes
NV Flash	64k bytes
Power	
Power adaptor	Input: AC 110V/220V, 50~60Hz
Power source	Output: DC 12V/2.6A
Cash drawer output	DC 12V/2A
Physical characteristics	
Weight	1.2KG
Dimensions	180×135×135mm (D×W×H)
Environmental Requirements	
Work environment	Temperature (0~45) humidity(10~80%)
Storage environment	Temperature(-10~60℃) humidity(10~80%)
Reliability	
Printer head life	100KM
Auto cutter	Yes