


P.C.B LAYOUT
TOP VIEW ± 0.05

PCB EDGE



CIRCUIT POSITION

INFORMATION

- 1.SWITCH TYPE: CARD OUT—SWITCH OPEN
CARD IN—SWITCH CONTACT

SIM CARD	
Pin No.	NAME
C1	VCC
C2	RST
C3	CLK
C4	Reserved
C5	GND
C6	VPP
C7	I/O
C8	Reserved

MICRO SD CARD			
Pin No.	NAME	TYPE	DESCRIPTION
1	DAT2	I/O/PP	Date Line[bit2]
2	CD/DAT3	I/O/PP	Card Detect Date Line[bit3]
3	CMD	PP	Command Response
4	VDD	S	Supply Voltage
5	CLK	I	Clock
6	VSS	S	Supply Voltage Ground
7	DAT0	I/O/PP	Date Line[bit0]
8	DAT1	I/O/PP	Date Line[bit1]

RoHS
Compliant

APPR.
核准 Betty

DWG.
製圖 Betty

DATE 制表日 2013/08/20



SCALE
比例 參考

UNIT
單位 MM
PAGE
張數 2 OF 4

TOLERANCE
容許公差

0 ± 0.30
30 ± 0.20
ANG. $\pm 3^\circ$

SIZE
紙張尺寸 A 4
REV.
版本 A

PART NAME 品名
TFLASH+SIM CARD SMT TYPE 16P
SELECTIVE GOLD 5U" PLATING
BLACK COLOR REEL PACKING ROHS

PART NO.
料號 C0633-16DEBR00R

HSM 玄茂科技股份有限公司
HSUAN MAO TECHNOLOGY CO., LTD.