

UC Headset Quotation					
No.	Item #	Photo	Specifications		Price (USD) FOB SZ
1	UC-001		Speaker Diameter	Ø30mm	US\$11.30
			Speaker Sensitivity	109dB ± 3dB	
			Impedance	32Ω	
			Frequency Response	20Hz-20000Hz	
			Microphone Sensitivity	-38dB ± 3dB	
			Microphone Frequency	100-10000Hz	
			Cable Length	1.9m ± 5%	
			Connector	Type-C + USB dapter	
2	UC-001(Black and Silver)		Speaker Diameter	Ø30mm	US\$11.60
			Speaker Sensitivity	109dB ± 3dB	
			Impedance	32Ω	
			Frequency Response	20Hz-20000Hz	
			Microphone Sensitivity	-38dB ± 3dB	
			Microphone Frequency	100-10000Hz	
			Cable Length	1.9m ± 5%	
			Connector	Type-C + USB dapter	
3	BT-001		Speaker Diameter	Ø30mm	US\$8.50
			Speaker Sensitivity	109dB ± 3dB	
			Impedance	32Ω	
			Operating Frequency	2.402-2.480GHz	
			Microphone Sensitivity	-38dB ± 3dB	
			Microphone Frequency	100-10000Hz	
			Battery Capacity	400mAh	
			Working time	> 20H	
			Charging time	1.5 hours	
4	BT-001(Black and Silver)		Speaker Diameter	Ø30mm	US\$8.80
			Speaker Sensitivity	109dB ± 3dB	
			Impedance	32Ω	
			Operating Frequency	2.402-2.480GHz	
			Microphone Sensitivity	-38dB ± 3dB	
			Microphone Frequency	100-10000Hz	
			Battery Capacity	400mAh	
			Working time	> 20H	
			Charging time	1.5 hours	
5	UC-002		Speaker Diameter	Ø30mm	US\$10.60
			Speaker Sensitivity	109dB ± 3dB	
			Impedance	32Ω	
			Frequency Response	20Hz-20000Hz	
			Microphone Sensitivity	-38dB ± 3dB	
			Microphone Frequency	100-10000Hz	
			Cable Length	1.9m ± 5%	
			Connector	Type-C + USB dapter	
6	UC-003		Speaker Diameter	Ø40mm	15
			Speaker Sensitivity	109dB ± 3dB	
			Impedance	32Ω	
			Frequency Response	20Hz-20000Hz	
			Microphone Sensitivity	-38dB ± 3dB	
			Microphone Frequency	100-10000Hz	
			Cable Length	1.9m ± 5%	
			Connector	Type-C + USB dapter	
7	UC-004		Speaker Diameter	Ø40mm	13.2
			Speaker Sensitivity	109dB ± 3dB	
			Impedance	32Ω	
			Frequency Response	20Hz-20000Hz	
			Microphone Sensitivity	-38dB ± 3dB	
			Microphone Frequency	100-10000Hz	
			Cable Length	1.9m ± 5%	
			Connector	Type-C + USB dapter	
8	UC-005		Speaker Diameter	Ø40mm	
			Speaker Sensitivity	109dB ± 3dB	
			Impedance	32Ω	
			Frequency Response	20Hz-20000Hz	
			Microphone Sensitivity	-38dB ± 3dB	
			Microphone Frequency	100-10000Hz	

			<table><tr><td>Battery Capacity</td><td>400mAh</td></tr><tr><td>Working time</td><td>> 20H</td></tr><tr><td>Charging time</td><td>1.5 hours</td></tr><tr><td>Effective Range</td><td>≥10 meters</td></tr></table>	Battery Capacity	400mAh	Working time	> 20H	Charging time	1.5 hours	Effective Range	≥10 meters									
Battery Capacity	400mAh																			
Working time	> 20H																			
Charging time	1.5 hours																			
Effective Range	≥10 meters																			
9	UC-392		<table><tr><td>Speaker Diameter</td><td>Ø40mm</td></tr><tr><td>Speaker Sensitivity</td><td>109dB ± 3dB</td></tr><tr><td>Impedance</td><td>32Ω</td></tr><tr><td>Frequency Response</td><td>20Hz-20000Hz</td></tr><tr><td>Microphone Sensitivity</td><td>-38dB ± 3dB</td></tr><tr><td>Microphone Frequency</td><td>100-10000Hz</td></tr><tr><td>Cable Length</td><td>1.9m ± 5%</td></tr><tr><td>Connector</td><td>Type-C + USB dapter</td></tr></table>	Speaker Diameter	Ø40mm	Speaker Sensitivity	109dB ± 3dB	Impedance	32Ω	Frequency Response	20Hz-20000Hz	Microphone Sensitivity	-38dB ± 3dB	Microphone Frequency	100-10000Hz	Cable Length	1.9m ± 5%	Connector	Type-C + USB dapter	US\$13.40
Speaker Diameter	Ø40mm																			
Speaker Sensitivity	109dB ± 3dB																			
Impedance	32Ω																			
Frequency Response	20Hz-20000Hz																			
Microphone Sensitivity	-38dB ± 3dB																			
Microphone Frequency	100-10000Hz																			
Cable Length	1.9m ± 5%																			
Connector	Type-C + USB dapter																			