

	1	2	3	4	5	6	7	8	9
G	SPECIFICATIONS						Recommended P.C.B Layout(Top Side) (PCB BOARD TOLERANCE±0.05)		
	Rated Current:3.0AMP								
	Contact Resistance:20mΩ Max								
	Withstand Voltage:1000V AC/DC								
	Insulation Resistance:1000MΩ Min								
	Operation Temperature:−40°c to +105°c								
F	Contact Material:Brass								
	Contact Plating:Au or Sn Over Ni								
	Insulator Material:Polyester(UL94V-0)								
	Standard: PBT								
E	Max.Processing Temp: 180°C for 30-60 seconds (200°C for 10 seconds)								
D									
C									
B									
A									

1

2

3

4

5

6

7

8

9

Rated Current:3.0AMP

Contact Resistance:20mΩ Max

Withstand Voltage:1000V AC/DC

Insulation Resistance:1000MΩ Min

Operation Temperature:−40°c to +105°c

Contact Material:Brass

Contact Plating:Au or Sn Over Ni

Insulator Material:Polyester(UL94V-0)

Standard: PBT

Max.Processing Temp: 180°C for 30-60 seconds
(200°C for 10 seconds)

2.54xNo.of Positions+0.6±0.3

2.54x(N-1)Positions±0.1

5.0±0.15

2.54

2.54x(N-1)Positions

0.1°

0.48

6.3

8.5±0.15

2.54±0.1

0.64x0.4

4.2±0.2

3.20±0.2

2.54±0.10

Ordering Information

2285 2 XX XX X R Y 01

No.of Pins Per Row
2*40
2-80

Contact Plating
G0:Gold Flash
G2:5U" Gold
G3:10U" Gold
G4:15U" Gold
G5:30U" Gold
S0:Gold Flash/Tin
SN:Tin

Insulator Material
Option
A=BK-PBT
B=BK-PA66
C=BK-PA6T
D=BK-PA46
F=BK-LCP

OPERATION

DRAW

YTYuSheng

12.03.28

SCALE

FIT

UNIT

mm

SIZE

A4

SHEET

1/1

PROJ.

◆

◀

TITLE:

2.54PF H8.5mm 2xNpin 90°

22852XXXXRY01

深圳市锦凌电子有限公司

SHENZHEN JINLING ELECTRONIC CO.,LTD

Tel: 86-755-2997-5806/5802 Fax: 86-755-2997-5992

JIN

SHENZHEN JINLING ELECTRONIC CO.,LTD

Tel: 86-755-2997-5806 /5802 Fax: 86-755-2997-5992

深圳市锦凌电子有限公司

22852XXXXRY01

2.54PF H8.5mm 2xNpin 90°