




Products Picture			
Model Number	NPL-05CR	NPL-07CR	NPL-09CR
Cooling Capacity (Btu)	5,000 BTU	7,000 BTU	9,000 BTU
Cooling Capacity (kw)	1.4	2	2.5
Heating Capacity (kw)	1.1	1.7	2.2
Power Supply	220-240V, 50Hz	220-240V, 50Hz	220-240V, 50Hz
Rated Input (Cooling/W)	550	760	960
Rated Current (Cooling/A)	2.5	3.3	4.2
Rated Input (Heating/W)	450	650	900
Rated Current (Heating/A)	1.7	2.8	3.9
EER for cooling	2.60	2.63	2.60
COP for heating	2.41	2.61	2.44
Refrigerant Charge	R290	R290	R290
Air Circulation (m ³ /h)	230	300	330
Noise (EER rated)	64dB(A)	64dB(A)	64dB(A)
Body Size (mm)	340*694*300	340*694*300	340*694*300
Carton Size (mm)	403*886*335	403*886*335	403*886*335
Net Weight (kg)	18.5	19.5	21.5
Gross Weight (kg)	21.5	22.5	24.5
Application Area (m ²)	6-10	8-12	12-16
Loading Quantity (pc) (20'/40'/40' HQ)	192 / 392 / 602	192 / 392 / 602	192 / 392 / 602
Control Type	Remote Control	Remote Control	Remote Control