



Shenzhen Easythread Technology Co., Ltd

Address: 501, Building A, No. 29, Jiangjunmao, Wulian Community, Longgang Street, Longgang District, Shenzhen, China

www.easythread.com

Email: sales01@easythread.com

Phone: +8613407062141 (wechat)

Easythread AS series 3D printer quotation

SPECIFICATIONS				
Model		AS1	AS2	AS3
TECH		FDM	FDM	FDM
Body	build volumn	265*265*260mm	185*185*185mm	270*270*270mm
	products size	445*470*550mm	330w*369d*400h mm	550 *485* 550MM
	package size	550*520*700mm	480 *480 *350mm	650* 600 *350mm
	frame	aluminum	aluminum	aluminum
	N.W	24kg	6kg	10kg
Print Head	Hot end	Metal	Metal	Metal
	Extruder gear	hardened steel	hardened steel	hardened steel
	Nozzle	0.4mm default (0.2/0.6/0.8mm optional)	0.4mm default (0.2/0.6/0.8mm optional)	0.4mm default (0.2/0.6/0.8mm optional)
	Nozzle Max temperature	300℃	300℃	300℃
	Filament	1.75mm	1.75mm	1.75mm
	Extrude	Near end	Near end	Near end
Heatbed	Platform	PEI Plate	PEI Plate	PEI Plate
	Max Temperature	100℃	70℃	100℃
Speed	Max speed	500mm/s	300mm/s	300mm/s
	Max speed	10000mm/s ²	10000mm/s ²	10000mm/s ²
	Maximum flow	25mm ³ /s	25mm ³ /s	25mm ³ /s
Cooling,air purifier	Print Cooling fan	Yes	Yes	Yes
	hotend cooling fan	Yes	Yes	Yes
	motherboard cooling fan	Yes	Yes	Yes
	cabin fan	Yes	/	/
	air purifier	Yes	/	/
Filament	Filament	PLA/ABS/PETG/PET/TPU	PLA/PETG/TPU	PLA/PETG/TPU
	4 colors ASM	Optional	Optional	Optional
Control	Camera	Yes	Optional	Optional
	Power cut, resume	Yes	Yes	Yes
	Filament breakage detection	Yes	Yes	Yes
	Automatic leveling	Yes	Yes	Yes
	radar	/	/	/
Power	Voltage	100-240V,50/60Hz	100-240V,50/60Hz	100-240V,50/60Hz
	Watt	360W	150W	360W
Interactive	Screen	4.3inch screen	2.4inch screen	3.2inch screen
	Print	U Disk/Wifi	U Disk/Wifi	U Disk/Wifi
	connection	WIFI/U Disk/Ethernet	WIFI/U Disk/Ethernet	WIFI/U Disk/Ethernet
Software	Slicer	OrcaSlicer	OrcaSlicer	OrcaSlicer
	Systme	Windows/MacOS	Windows/MacOS	Windows/MacOS