

1	2	3	4	5	6	7	8	9
SPECIFICATIONS						Recommended P.C.B Layout(Top Side) (PCB BOARD TOLERANCE±0.05)		
G Rated Current:3.0AMP Contact Resistance:20mΩ Max Withstand Voltage:1000V AC/DC Insulation Resistance:1000MΩ Min Operation Temperature:-40°c to +105°c								
F Contact Material:Brass Contact Plating:Au or Sn Over Ni Insulator Material:Polyester(UL94V-0) Standard: PA6T Max.Processing Temp: 230℃ for 30-60 seconds (260℃ for 10 seconds)								
E								
D Ordering Information 2285 2 XX XX X M Y 01								
C No.of Pins Per Row 2-80 Contact Plating 60:Gold Flash Insulator Material Option A=BK-PBT B=BK-PA66 C=BK-PA6T D=BK-PA66 F=BK-LCP SN:Tin								
B								
A								
REV 1						2		
DATE 2012.03.28						3		
MODIFICATION DESCRIPTION NEW DRAWING						4		
CHANGE						5		
DIM TOL						6		
APPROVE						7		
YTYuSheng						8		
12.03.28						9		
SCALE								
FIT								
UNIT								
SIZE								
SHEET								
PROJ.								
TITLE:								
PART NO.								
22852XXXXXXMY01								
2.54PF H8.5mm 2xNpin SMT W8.3								
SHENZHEN JINLING ELECTRONIC CO.,LTD								
Tel: 86-755-2997-5806/5802 Fax: 86-755-2997-5992								

1	2	3	4	5	6	7	8	9
SPECIFICATIONS						Recommended P.C.B Layout(Top Side) (PCB BOARD TOLERANCE±0.05)		
G Rated Current:3.0AMP								
Contact Resistance:20mΩ Max								
Withstand Voltage:1000V AC/DC								
Insulation Resistance:1000MΩ Min								
Operation Temperature:-40℃ to +105℃								
F Contact Material:Brass								
Contact Plating: Au or Sn Over Ni								
Insulator Material: Polyester(UL94V-0)								
Standard: PA6T								
Max.Processing Temp: 230℃ for 30-60 seconds (260℃ for 10 seconds)								
D						D		
C						C		
B						B		
A						A		
Ordering Information								
2285 2 XX XX X M Y 01								
No.of Pins Per Row 2-40								
Contact Plating 60:Gold Flash								
Insulator Material Option								
A=BK-PBT								
B=BK-PA66								
C=BK-PA6T								
D=BK-PA66								
F=BK-LCP								
G5:30U" Gold								
G4:15U" Gold								
G3:10U" Gold								
G2:5U" Gold								
G0:Gold Flash								
S0:Gold Flash/Tin								
SN:Tin								
OPERATION						SCALE		
DRAW						FIT		
YTYuSheng						12.03.28		
X.X						UNIT		
±0.30						mm		
X.XX						SIZE		
±0.20						A4		
X.XXX						SHEET		
±0.10						1/1		
Angle						TITLE:		
±3°						PART NO.		
APPROVE						22852XXXXXXMY01		
DIM TOL						2.54PF H8.5mm 2xNpin SMT W8.3		
CHANGE								
MODIFICATION DESCRIPTION								
DATE								
REV								
2012.03.28								
NEW DRAWING								
1						2		
2						3		
3						4		
4						5		
5						6		
6						7		
7						8		
8						9		