



✓RoHS Printer Cable IEEE1284, DB25 / HPCN36

Art No..X	Plug	Length
260504.X	DB25 Plug / HP Centronic 36 Plug	1, 2, 3, 5M

- UL20276 18 Twisted Pair
- Double Shielded
- Hood Moldings have internal 360°C Shields
- Moulded

✓RoHS Printer Cable IEEE1284, DB25 / CN36

Art No..X	Plug	Length
260503.X	DB25 Plug / Centronic 36 Plug	1, 2, 3, 5, 10M

- UL20276 18 Twisted Pair
- Double Shielded
- Hood Moldings have internal 360°C Shields
- Moulded



✓RoHS Bi-directional Parallel Printer Cable

Art No..X	Plug	Length
260501.X	DB25 Plug / Centronic 36 Plug	1, 2, 3, 5, 10M

- UL2464 25Cores
- Fully Shielded
- Moulded

✓RoHS Serial Cable for Laser Printer

Art No..X	Plug	Length
260502.X	DB25 Plug / DB9 Socket	1, 2, 3, 5M

- UL 2464 7 Cores
- Fully Shielded
- Moulded
- Pin Assignment Details is as →

Assignment	
DB25 Plug	DB9 Socket
04	01
02	02
03	03
05,06	04
07	05
20	06,08
08	07
S	S

