

UL3265

产品说明

- 额定温度:125℃
- 额定电压:150V
- 参考标准:UL758,UL1581,CSA C22.2No.210.2
- 导体使用单支或绞合 32~16AWG 镀锡或裸铜
- XLPE 绝缘, 符合ROHS 环保标准
- 通过UL水平及CSA FT2 阻燃测试
- 绝缘厚度均匀、易裁线、易剥皮
- 用于一般电子、电器设备内部连接线

PRODUCT DESCRIPTION

- Rated temperature: 125℃
- Rated voltage: 150V
- Reference standard: UL758,UL1581,CSA C22.2No.210.2
- Solid or stranded ,tinned or bare copper conductor 32~16AWG
- XLPE insulation ,comply with ROHS environmental standard
- Passes UL Horizontal and CSA FT2 flame test
- Uniform insulation thickness to ensure easy stripping and cutting
- For general purpose internal wiring of appliance



印字 MARKING

AWM 3265 E330484 125℃ 150V **AWG B&T CABLE c AWM I A FT2 125℃ 150V **AWG

产品结构 CABLE CONSTRUCTION

编号	导体 CONDUCTOR			绝缘 INSULATION	完成外径Overall diameter(mm)		最大导体电阻 MAX. COND. RESIS TANCE Ω /km, (20℃, DC)	参考 重量 Approx. weight (g/m)	参考 包装 Standard packing (m)
	规格 SIZE	构造 CONSTRUCTIO N (No. /mm)	外径 DIA (mm)	厚度 THICKNESS (mm)	标准Standard	公差 Tolerance			
F32653207XX	32	7/0.08	0.24	0.26	0.80	±0.1	556	0.97	2440
F326532070SXX	32	7/0.08 OS=1	0.24	0.26	0.80	±0.1			
F32653201XX	32	1/0.20	0.2	0.26	0.75	±0.1			
F32653007XX	30	7/0.10	0.30	0.26	0.85	±0.1	381	1.22	2440
F326530070SXX	30	7/0.10 OS=1	0.30	0.26	0.85	±0.1			
F32653001XX	30	1/0.254	0.254	0.26	0.80	±0.1			
F32652807XX	28	7/0.127	0.38	0.26	0.90	±0.1	239	1.57	1830
F32652807XX	28	7/0.127 OS=1	0.38	0.26	0.90	±0.1			
F32652801XX	28	1/0.32	0.32	0.26	0.85	±0.1			
F32652607XX	26	7/0.16	0.48	0.26	1.00	±0.1	150	1.93	1220
F32652601XX	26	1/0.40	0.40	0.26	0.95	±0.1			
F32652411XX	24	11/0.16	0.61	0.26	1.15	±0.1			
F32652407XX	24	7/0.20	0.60	0.26	1.15	±0.1	94.2	3.14	1220
F326524070SXX	24	7/0.20 OS=1	0.60	0.26	1.15	±0.1			
F32652401XX	24	1/0.51	0.51	0.26	1.05	±0.1			
F32652217XX	22	17/0.16	0.76	0.26	1.30	±0.1	60.16	4.5	610
F32652207XX	22	7/0.254	0.76	0.26	1.30	±0.1			
F326522070SXX	22	7/0.254 OS=1	0.76	0.26	1.30	±0.1			
F32652201XX	22	1/0.64	0.64	0.26	1.20	±0.1	38.58	6.49	610
F32652026XX	20	26/0.16	0.94	0.26	1.50	±0.1			
F32652010XX	20	10/0.254	0.94	0.26	1.50	±0.1			
F32652007XX	20	7/0.32	0.94	0.26	1.50	±0.1			
F32652001XX	20	1/0.813	0.813	0.26	1.35	±0.1		5.9	

F32651841XX	18	41/0.16	1.20	0.26	1.75	±0.1	22.98	9.7	610
F32651816XX	18	16/0.254	1.20	0.26	1.75	±0.1		9.6	
F32651801XX	18	1/1.024	1.024	0.26	1.55	±0.1		8.82	
F32651626XX	16	26/0.254	1.50	0.26	2.05	±0.1	15.06	14.74	610
F32651601XX	16	1/1.29	1.29	0.26	1.85	±0.1		13.57	

备注：XX代表颜色，01黑色02白色03灰色04橙色05绿色06红色07蓝色08黄色09棕色10紫色11粉色；双色线用4位表示，前面部分为主色，例如白/黑，0201