

PRODUCT DESCRIPTION

- Rated temperature: 70℃
- Rated voltage: 300/300V
- Reference standard: DIN VDE 0281-5
- Stranded bare copper conductor 0.5~0.75mm²
- PVC insulation , comply with ROHS environmental standard
- PVC jacket , comply with ROHS environmental standard
- Passes HD 405.1 flame test
- Uniform insulation thickness to ensure easy stripping and cutting
- For general purpose use for power supply cord

CABLE CONSTRUCTION

CONDUCTOR					INSULATION		JACKET		MAX. COND. RESISTANCE (Ω /km, 20, DC) °C
STYLE	CROSS SECTION (mm ²)	CONSTRUCTION (No. /mm)	DIA. (mm)	(No.)	INSULATION THICKNESS (mm)	O. D. (mm)	JACKET THICKNESS (mm)	O. D. (mm)	
H03VVH2-F	0.50	28/0.15	0.92	2.00	0.54	2.00	0.65	3.30×5.30	39.00
	0.75	24/0.20	1.13	2.00	0.51	2.15	0.68	3.50×5.70	26.00
H03VVH3-F	0.50	28/0.15	0.92	2.00	0.54	2.00	0.65	5.30	39.00
				3.00	0.54	2.00	0.65	5.60	
	0.75	24/0.20	1.13	2.00	0.51	2.15	0.63	5.60	26.00
				3.00	0.51	2.15	0.63	5.90	

