



TAKFLY COMMUNICATIONS CO., LTD.

ADD: Takfly Industrial Park, Tongsheng Community, Dalang Street, Longhua District, Shenzhen, 518109, China.

Tel: +86-755-28106528

Fax: +86-755-23777278

Compact Coarse Wavelength Division Multiplexer

Features

- Low Insertion Loss
- Compact size
- Ultra Stable and Highly Reliable
- Extended Operating Temperature Available



Applications

- Optical Add/Drop Multiplexing
- Telecom networks
- Metro networks
- Broadband Networks



Performance Specifications

Parameter		4 Ch	4+UPG	8 Ch	8+UPG1	8+UPG2
Operating Wavelength (nm)		1260~1620				
Channel Wavelength (nm)		1270,1290,...,1590,1610, or 1271,1291,...,1591,1611				
UPG Port Wavelength Range(nm)		NA	TBD	NA	1260~1360	1260~1457
Channel Spacing(nm)		20				
Channel Passband (nm)		CWL+/-6.5nm				
Insertion Loss (dB)*		≤0.8	≤0.8	≤1.4	≤1.4	≤1.7
Channel Ripple (dB)		≤0.3				
Isolation (dB)	Adjacent	>30				
	Non-adjacent	>40				
UPG Isolation (dB)		NA	>15	NA	>15	>15
Polarization Mode Dispersion (PS)		≤0.2				
Polarization Dependent Loss (dB)		≤0.2				
Directivity (dB)		>45				
Return Loss (dB)		>45				
Maximum Power Handling (mW)		500				
Operating Temperature (°C)		-5~+70				
Storage Temperature (°C)		-40~85				
Fiber Type		G657A1				
Connector		TBD				
Package dimension (mm)		L55 x W45 x H6 or L44 x W25 x H6				

Above specification are for device without connector.




TAKFLY COMMUNICATIONS CO., LTD.

ADD: Takfly Industrial Park, Tongsheng Community, Dalang Street, Longhua District, Shenzhen, 518109, China.
Tel: +86-755-28106528 Fax: +86-755-23777278

Order Information

Configuration	Channel No.	Pigtail Type	Fiber length	Declension (mm)	Connector
CC=CCWDM	40=4 Channel 41=4+UPG 80=8 Channel 81=8+UPG1 82=8+UPG2	0=250um 1=900um	0=0.5m 1=1m 2=1.5m 3=others	1= L55 x W45 x H6 2=L44 x W25 x H6	0=None 1=FC/APC 2=FC/PC 3=SC/APC 4=SC/PC 5=others

Type1:



Type 2:

