




- 技术要求:
1. 产品外观光滑，平整，不得有划伤残缺等不良现象
 2. 所有材质符合ROHS环保要求
 3. 耐压60VDC, 额定电流5A, 耐温120°C
 4. 插拔力5-30N, 寿命5000次
 5. “*”重点管控尺寸

				TOLERANCE								
				UNLESS SPECIFIED		A1	2020.07.27	\triangle 修改焊肢尺寸19.0至19.4		GYW		
				UP TO 5mm: \pm 0.1	ANGULAR	A0	2019.10.25	首次发行		GYW		
				ABOVE 5mm: \pm 0.2	$\pm 1^\circ$	NO	DATE	REVISIONS		BY	APPD	
3	RTC30-02APU+PB 2#	PBS/PBT4130	1	Ag PLATED/BLACK	TITLE: DC JACK			UNIT : MM	ROHS	DWN		
2	RTC30-01APU-PIN 1#	PBS	1	Ag PLATED	MODEL: RT-C30-BA			SCALE: 6:1	COMPLIANT	CHK'D		
1	RTC30-BAPB-B00	PBT4130	1	BLACK	 HAOYU(HONGKONG)LIMITED 皓宇(香港)有限公司			APPD				
NO.	PART NAME	MATERIAL	QTY	FINISHING				PRO.AGL:  		REV :A1		