

- 材料: 45# / 40Cr / 316L
Material: 1045 / 5140 / 316L
- 表面处理: 锌镍合金
三价环保锌
防锈
Surface: Zinc-Nickel Plating
Cr3+Plating
oiled


订货代号 Ordering Codes	规格 Nominal Size		尺寸(mm) Dimensions(mm)										螺栓 Bolts	
	ISO [DN]	SAE [inch]	A	B	C	D	E	F	G	H	I	J	公制 metr.	UNC

标准系列 (按ISO6162-1) Standard Pressure Series (According to ISO6162-1) 3000 PSI Series

PC-DK301	13	1/2"	38.1	17.5	54	45.6	8.7	31	24.3	6.2	13	19	M8	5/16"-18
PC-DK302	19	3/4"	47.6	22.3	65	51.8	10.5	38.9	32.2	6.2	14	22	M10	3/8"-16
PC-DK303	25	1"	52.4	26.2	70	58.4	10.5	45.3	38.5	7.5	16	24	M10	3/8"-16
PC-DK304	32	1 1/4"	58.7	30.2	79.5	72.6	12	51.6	43.7	7.5	14	24	M12	7/16"-14
PC-DK305	38	1 1/2"	69.9	35.7	94	82.2	13.5	61.1	50.8	7.5	16	25	M12	1/2"-13
PC-DK306	51	2"	77.8	42.9	102	96.4	13.5	72.3	62.8	9	16	26	M12	1/2"-13
PC-DK307	64	2 1/2"	88.9	50.8	114.5	108.2	13.5	84.9	74.9	9	19	38	M12	1/2"-13
PC-DK308	76	3"	106.4	61.9	135	130.6	17	102.4	90.9	9	22	41	M16	5/8"-11
PC-DK309	89	3 1/2"	120.7	69.9	152	139.2	17	115.1	102.4	10.7	22	28	M16	5/8"-11
PC-DK310	102	4"	130.2	77.8	162	151.8	17	127.8	115	10.7	25	35	M16	5/8"-11
PC-DK311	127	5"	152.4	92.1	184	180.8	17	153.2	140.5	10.7	28	41	M16	5/8"-11

高压系列 (按ISO6162-2) High Pressure Series (According to ISO6162-2) 6000 PSI Series

PC-DK601	13	1/2"	40.5	18.2	56.5	47.2	8.7	32.5	24.6	7.2	16	22	M8	5/16"-18
PC-DK602	19	3/4"	50.8	23.8	71	60	10.5	42	32.5	8.2	19	28	M10	3/8"-16
PC-DK603	25	1"	57.2	27.8	81	69.6	11.9	48.4	38.8	9	24	33	M12	7/16"-14
PC-DK604	32	1 1/4"	66.6	31.8	95	77.2	13.5	54.8	44.5	9.8	27	38	M12	1/2"-13
PC-DK605	38	1 1/2"	79.3	36.5	113	95	17	64.3	51.6	12	30	43	M16	5/8"-11
PC-DK606	51	2"	96.8	44.5	133	113.8	21	80.2	67.6	12	37	52	M20	3/4"-10



- 材料: 45# / 40Cr / 316L
Material: 1045 / 5140 / 316L
- 表面处理: 锌镍合金
三价环保锌
防锈
Surface: Zinc-Nickel Plating
Cr3+Plating
oiled

订货代号 Ordering Codes	规格 Nominal Size		尺寸(mm) Dimensions(mm)										螺栓 Bolts	
	ISO [DN]	SAE [inch]	A	B	C	D	E	F	G	H	I	J	公制 metr.	UNC

标准系列 (按ISO6162-1) Standard Pressure Series (According to ISO6162-1) 3000 PSI Series

PC-NK301	13	1/2"	38.1	17.5	54	45.6	8.7	31	24.3	6.2	13	19	M8	5/16"-18
PC-NK302	19	3/4"	47.6	22.3	65	51.8	10.5	38.9	32.2	6.2	14	22	M10	3/8"-16
PC-NK303	25	1"	52.4	26.2	70	58.4	10.5	45.3	38.5	7.5	16	24	M10	3/8"-16
PC-NK304	32	1 1/4"	58.7	30.2	79.5	72.6	12	51.6	43.7	7.5	14	24	M12	7/16"-14
PC-NK305	38	1 1/2"	69.9	35.7	94	82.2	13.5	61.1	50.8	7.5	16	25	M12	1/2"-13
PC-NK306	51	2"	77.8	42.9	102	96.4	13.5	72.3	62.8	9	16	26	M12	1/2"-13
PC-NK307	64	2 1/2"	88.9	50.8	114.5	108.2	13.5	84.9	74.9	9	19	38	M12	1/2"-13
PC-NK308	76	3"	106.4	61.9	135	130.6	17	102.4	90.9	9	22	41	M16	5/8"-11
PC-NK309	89	3 1/2"	120.7	69.9	152	139.2	17	115.1	102.4	10.7	22	28	M16	5/8"-11
PC-NK310	102	4"	130.2	77.8	162	151.8	17	127.8	115	10.7	25	35	M16	5/8"-11
PC-NK311	127	5"	152.4	92.1	184	180.8	17	153.2	140.5	10.7	28	41	M16	5/8"-11

高压系列 (按ISO6162-2) High Pressure Series (According to ISO6162-2) 6000 PSI Series

PC-NK601	13	1/2"	40.5	18.2	56.5	47.2	8.7	32.5	24.6	7.2	16	22	M8	5/16"-18
PC-NK602	19	3/4"	50.8	23.8	71	60	10.5	42	32.5	8.2	19	28	M10	3/8"-16
PC-NK603	25	1"	57.2	27.8	81	69.6	11.9	48.4	38.8	9	24	33	M12	7/16"-14
PC-NK604	32	1 1/4"	66.6	31.8	95	77.2	13.5	54.8	44.5	9.8	27	38	M12	1/2"-13
PC-NK605	38	1 1/2"	79.3	36.5	113	95	17	64.3	51.6	12	30	43	M16	5/8"-11
PC-NK606	51	2"	96.8	44.5	133	113.8	21	80.2	67.6	12	37	52	M20	3/4"-10