










XIANGRUN		contact /tel.:	MIA +86 13539056172
GUANGDONG,DONGGUAN,CHINA			mia@xiangrundg.com
Product No.	Picture	Specification	Cert./Test Report
XR-UTU1A2C20		<p>US TO US USB 2C1A GaN 20W ANTI SURGE NTC Lightning Protection MOV 2500V Shell material: PC 94V-0 fire retardant, Metal Material:Pure copper 1 X 3PIN AC Outlet 2 X 2PIN AC Outlet 1875W Power Rate</p> <p>AC OUTPUT 15A 125V,1875W DC OUTPUT USB-C1 / C2 + USB-A C1/C2:PDO 5V=3.0A,9V=2.22A,12V=1.67A,20W USB-A:QC 5V=3.0A,9V=2.0A,12V=1.5A,18W C1+C2+A1 Total:5V=3.1A,15.5W SIZE:76.2mm*55.2m *38.5mm Color: White, Purple, Blue, Green, Pink,Black</p>	<p>UL498, UL498A socket CSA UL 62368-DC module EN 55032-DC module EN IEC 61000-3-2-DC module EN 61000-3-3-DC module EN 55035-DC module DOE North American Energy Efficiency CEC - Canadian Energy Efficiency ERP - European Energy Efficiency</p>
XR-ETU1A2C20		<p>EU TO US USB 2C1A GaN 20W ANTI SURGE NTC Lightning Protection MOV 2500V Shell material: PC 94V-0 fire retardant, Metal Material:Pure copper 1 X 3PIN AC Outlet 2 X 2PIN AC Outlet 3750W Power Rate</p> <p>AC OUTPUT 15A 250V,3750W DC OUTPUT USB-C1 / C2 + USB-A C1/C2:PDO 5V=3.0A,9V=2.22A,12V=1.67A,20W USB-A:QC 5V=3.0A,9V=2.0A,12V=1.5A,18W C1+C2+A1 Total:5V=3.1A,15.5W SIZE:76.2mm*55.2m *38.5mm Color: White, Purple, Blue, Green, Pink,Black</p>	<p>UL498, UL498A socket CSA UL 62368-DC module EN 55032-DC module EN IEC 61000-3-2-DC module EN 61000-3-3-DC module EN 55035-DC module DOE North American Energy Efficiency CEC - Canadian Energy Efficiency ERP - European Energy Efficiency</p>
XR-KTU1A2C20		<p>UK TO US USB 2C1A GaN 20W ANTI SURGE NTC Lightning Protection MOV 2500V Shell material: PC 94V-0 fire retardant, Metal Material:Pure copper 1 X 3PIN AC Outlet 2 X 2PIN AC Outlet 3250W Power Rate</p> <p>AC OUTPUT 13A 250V,3250W DC OUTPUT USB-C1 / C2 + USB-A C1/C2:PDO 5V=3.0A,9V=2.22A,12V=1.67A,20W USB-A:QC 5V=3.0A,9V=2.0A,12V=1.5A,18W C1+C2+A1 Total:5V=3.1A,15.5W SIZE:76.2mm*55.2m *38.5mm Color: White, Purple, Blue, Green, Pink,Black</p>	<p>UL498, UL498A socket CSA UL 62368-DC module EN 55032-DC module EN IEC 61000-3-2-DC module EN 61000-3-3-DC module EN 55035-DC module DOE North American Energy Efficiency CEC - Canadian Energy Efficiency ERP - European Energy Efficiency</p>
XR-UTK1A2C20		<p>US TO UK USB 2C1A GaN 20W ANTI SURGE NTC Lightning Protection MOV 2500V Shell material: PC 94V-0 fire retardant, Metal Material:Pure copper 1 X 3PIN AC Outlet 2 X 2PIN AC Outlet 3250W Power Rate</p> <p>AC OUTPUT 13A 250V,3250W DC OUTPUT USB-C1 / C2 + USB-A C1/C2:PDO 5V=3.0A,9V=2.22A,12V=1.67A,20W USB-A:QC 5V=3.0A,9V=2.0A,12V=1.5A,18W C1+C2+A1 Total:5V=3.1A,15.5W SIZE:76.2mm*55.2m *38.5mm Color: White, Purple, Blue, Green, Pink,Black</p>	<p>UL498, UL498A socket CSA UL 62368-DC module EN 55032-DC module EN IEC 61000-3-2-DC module EN 61000-3-3-DC module EN 55035-DC module DOE North American Energy Efficiency CEC - Canadian Energy Efficiency ERP - European Energy Efficiency</p>
XR-ETK1A2C20		<p>EU TO UK USB 2C1A GaN 20W ANTI SURGE NTC Lightning Protection MOV 2500V Shell material: PC 94V-0 fire retardant, Metal Material:Pure copper 1 X 3PIN AC Outlet 2 X 2PIN AC Outlet 3250W Power Rate</p> <p>AC OUTPUT 13A 250V,3250W DC OUTPUT USB-C1 / C2 + USB-A C1/C2:PDO 5V=3.0A,9V=2.22A,12V=1.67A,20W USB-A:QC 5V=3.0A,9V=2.0A,12V=1.5A,18W C1+C2+A1 Total:5V=3.1A,15.5W SIZE:76.2mm*55.2m *38.5mm Color: White, Purple, Blue, Green, Pink,Black</p>	<p>UL498, UL498A socket CSA UL 62368-DC module EN 55032-DC module EN IEC 61000-3-2-DC module EN 61000-3-3-DC module EN 55035-DC module DOE North American Energy Efficiency CEC - Canadian Energy Efficiency ERP - European Energy Efficiency</p>
XR-KTK1A2C20		<p>UK TO UK USB 2C1A GaN 20W ANTI SURGE NTC Lightning Protection MOV 2500V Shell material: PC 94V-0 fire retardant, Metal Material:Pure copper 1 X 3PIN AC Outlet 2 X 2PIN AC Outlet 3250W Power Rate</p> <p>AC OUTPUT 13A 250V,3250W DC OUTPUT USB-C1 / C2 + USB-A C1/C2:PDO 5V=3.0A,9V=2.22A,12V=1.67A,20W USB-A:QC 5V=3.0A,9V=2.0A,12V=1.5A,18W C1+C2+A1 Total:5V=3.1A,15.5W SIZE:76.2mm*55.2m *38.5mm Color: White, Purple, Blue, Green, Pink,Black</p>	<p>UL498, UL498A socket CSA UL 62368-DC module EN 55032-DC module EN IEC 61000-3-2-DC module EN 61000-3-3-DC module EN 55035-DC module DOE North American Energy Efficiency CEC - Canadian Energy Efficiency ERP - European Energy Efficiency</p>

<p>XR-UTV1A2C20</p>		<p>US TO UNIVERSAL USB 2C1A GaN 20W ANTI SURGE NTC Lightning Protection MOV 2500V Shell material: PC 94V-0 fire retardant, Metal Material:Pure copper 1 X 3PIN AC Outlet 2 X 2PIN AC Outlet 3750W Power Rate</p> <p>AC OUTPUT 15A 250V,3750W DC OUTPUT USB-C1 / C2 + USB-A C1/C2:PDO 5V=3.0A,9V=2.22A,12V=1.67A,20W USB-A:QC 5V=3.0A,9V=2.0A,12V=1.5A,18W C1+C2+A1 Total:5V=3.1A,15.5W SIZE:76.2mm*55.2m *38.5mm Color: White, Purple, Blue, Green, Pink, Black</p>	<p>UL498, UL498A socket CSA UL 62368-DC module EN 55032-DC module EN IEC 61000-3-2-DC module EN 61000-3-3-DC module EN 55035-DC module DOE North American Energy Efficiency CEC - Canadian Energy Efficiency ERP - European Energy Efficiency</p>
<p>XR-ETV1A2C20</p>		<p>EU TO UNIVERSAL USB 2C1A GaN 20W ANTI SURGE NTC Lightning Protection MOV 2500V Shell material: PC 94V-0 fire retardant, Metal Material:Pure copper 1 X 3PIN AC Outlet 2 X 2PIN AC Outlet 4000W Power Rate</p> <p>AC OUTPUT 16A 250V,4000W DC OUTPUT USB-C1 / C2 + USB-A C1/C2:PDO 5V=3.0A,9V=2.22A,12V=1.67A,20W USB-A:QC 5V=3.0A,9V=2.0A,12V=1.5A,18W C1+C2+A1 Total:5V=3.1A,15.5W SIZE:76.2mm*55.2m *38.5mm Color: White, Purple, Blue, Green, Pink,Black</p>	<p>UL498, UL498A socket CSA UL 62368-DC module EN 55032-DC module EN IEC 61000-3-2-DC module EN 61000-3-3-DC module EN 55035-DC module DOE North American Energy Efficiency CEC - Canadian Energy Efficiency ERP - European Energy Efficiency</p>
<p>XR-KTV1A2C20</p>		<p>UK TO UNIVERSAL USB 2C1A GaN 20W ANTI SURGE NTC Lightning Protection MOV 2500V Shell material: PC 94V-0 fire retardant, Metal Material:Pure copper 1 X 3PIN AC Outlet 2 X 2PIN AC Outlet 3250W Power Rate</p> <p>AC OUTPUT 13A 250V,3250W DC OUTPUT USB-C1 / C2 + USB-A C1/C2:PDO 5V=3.0A,9V=2.22A,12V=1.67A,20W USB-A:QC 5V=3.0A,9V=2.0A,12V=1.5A,18W C1+C2+A1 Total:5V=3.1A,15.5W SIZE:76.2mm*55.2m *38.5mm Color: White, Purple, Blue, Green, Pink Black</p>	<p>UL498, UL498A socket CSA UL 62368-DC module EN 55032-DC module EN IEC 61000-3-2-DC module EN 61000-3-3-DC module EN 55035-DC module DOE North American Energy Efficiency CEC - Canadian Energy Efficiency ERP - European Energy Efficiency</p>