

Mini PC Specification:

Mini PC model	HD4001 (silver and black optional)	
Mini PC size	196mm(L)*196mm(W)*32mm(H)	
Power supply	1*DC_IN	The inner diameter of the DC head is 2.5mm, it is recommended to use 12V7A or above power supply
CPU	Support integrated Intel Celeron and CORE 2~14th generation i3, i5, i7 (Please consult us for specific requirements.)	
Memory	Single channel DDR3 8G MAX; Dual channel DDR3 16G MAX; Dual channel DDR4 32G/64G MAX; (depending on configuration)	
Network function	1*LAN	Integrated Realtek 8111E/8111F/8111H Gigabit LAN, support wake-up on LAN, network PXE function.
	Support WIFI/3G/4G, support 2*WIFI antenna mast	
Display function	1*VGA	Support 2K resolution 1920*1080@60Hz
	1*HDMI	J1900 and 2nd and 3rd generations: Support 2K resolution 1920*1080@60Hz
		6th generation~10th generation: Support 4K resolution 4096/3840*2160@30Hz; 11th generation~14th generation: Support 4K resolution 4096/3840*2160@60Hz
USB function	2*USB3.0	The blue group USB is USB3.0 speed
	4*USB2.0	Black group USB is USB2.0 speed
Serial port function	2*COM	Support RS232/RS422/RS485 optional
Sound function	Integrated Realtek ALC662 HD digital audio decoder, 6-channel high-fidelity audio controller	
	1*SPK	Support audio output
	1*MIC	Support microphone input
	HDMI interface supports HDMI audio output	
Hard disk function	2.5-inch SSD disk, notebook hard disk, MSATA disk, M.2; (8G/16G/32G/64G/120G/128G/240G/256G, etc.)	
Switch function	POWER	switch button
Operating environment	Working temperature: -20℃~60℃; Working humidity: 5%~95% relative humidity, non-condensing	
BIOS	AMI BIOS, support power-on boot, scheduled boot, remote boot	
Watch dog	Watchdog programming, support hardware reset function (256 levels, 0~255 seconds)	
Operating system	Support Windows 11, Windows 10, Windows 8, Windows 7, Windows XP, Linux, etc.	