

Spec. (Dia.x Length mm)	Volume(m³)	Capacity (t/h)	Gradient(%)	Highest Inlet Air Temperature(°C)	Rotate Speed(r/min)	Main Motor(kw)
Φ600x6000	1.7	0.5-1.5	3~5	700~800	3~8	3
Φ800x8000	4.1	0.8-2.0	3~5	700~800	3~8	4
Φ800x10000	5.1	0.8-2.5	3~5	700~800	3~8	4
Φ1000x10000	7.9	1.0-3.0	3~5	700~800	3~8	7.5
Φ1000x12000	9.4	1.2-3.2	3~5	700~800	3~8	11
Φ1200x8000	9	1.9-2.4	3~5	700~800	3~8	7.5
Φ1200x10000	11.3	2.2-3.0	3~5	700~800	3~8	7.5
Φ1200x12000	13.6	2.4-3.2	3~5	700~800	3~8	7.5
Φ1500x12000	21.2	4.5-5.7	3~5	700~800	2~6	15
Φ1500x14000	24.7	5.3-6.6	3~5	700~800	2~6	15
Φ1500x16000	26.5	5.7-7.1	3~5	700~800	2~6	15
Φ1800x12000	30.5	6.5-8.1	3~5	700~800	2~6	18.5
Φ1800x14000	35.6	7.6-9.5	3~5	700~800	2~6	18.5
Φ1800x16000	40.7	7.8-10.2	3~5	700~800	2~6	18.5
Φ2000x18000	56.5	8.4-12.3	3~5	700~800	1.5~6	22