

**Specification**

Part Number(s)	S / N: C 2 1 1 7001
Enclosure Color	Black
Touch Technology & Capacity	Resistive or Projected Capacitive – multi touch
Diagonal Size	17" diagonal, Active matrix TFT LCD (LED)
Active Area (mm)	13.30" x 10.64" /337.92(H) x 270.336(V)
Aspect Ratio	4:3
Resolution	1280 x 1024 , 60HZ
Number of Colors	16.7 million
Brightness (typical)	LCD Panel: 250 nits
Response Time-total (typical)	3.8/1.2 (Typ.)(Tr/Td) ms
Contrast Ratio	1000:1
Touch Interface	USB
On Screen Display	<p>Controls: Menu, Power, UP, Down, Select</p> <p>Setting: brightness, contrast, clock, Phase, H-position, V-position, Auto-Adjust, Aspect Ratio, Sharpness, Color Temperature...</p> <p>Languages: Simplified Chinese, Traditional Chinese, English,Russian.Spanish</p> <p>Lockouts: OSD, Power</p>
Speakers	Without speakers
Input video format	PC-RGB
Input video frequency	Up to 1920x1080@60Hz
Input Voltage	DC 12V

Input Connector	HDMI /VGA
Monitor Dimensions (without stand)	386X320X46.5mm
Monitor Dimensions (with Stand)	425.3X357.14X49.8
Shipping Box Dimensions	435(17.13)X155(6.10)X395(15.55)
Weight (Unpackaged)	4.23KG
Weight (Packaged)	5.65KG

What's in the box	Touch monitor VGA cable USB cable HDMI cable Power code Power adapter User manual
-------------------	---

Parameter.	Available Adjustment
Brightness	0 ~ 1 0 0
Contrast	0 ~ 1 0 0
Clock	0 ~ 1 0 0
Phase	0 ~ 1 0 0
Auto Adjust	
H-position	0 ~ 1 0 0
V-position	0 ~ 1 0 0
Aspect Ratio	4 : 3
Sharpness	4 strings
Color Temperature	U s e r / W a r m / C o o l

<b>Defa</b>	
<b>OSD H-Position</b>	0 ~ 1 0 0
<b>OSD V-Position</b>	0 ~ 1 0 0
<b>OSD Timeout</b>	1 0 – 1 2 0 s
<b>Recall Defaults</b>	1 0 s
<b>Video Priority</b>	P C – R G B
<b>Touch on Sleep</b>	3 – 5 m s
<b>Touch Through</b>	>80%