



|                                         |                                                                                                                                                                                                                          |
|-----------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Printer Model</b>                    | DTP350                                                                                                                                                                                                                   |
| <b>Resolution</b>                       | 203 DPI (8 dot/mm)                                                                                                                                                                                                       |
| <b>Printing Method</b>                  | Direct Thermal                                                                                                                                                                                                           |
| <b>Printing head temperature sensor</b> | Thermal sensitive resistance                                                                                                                                                                                             |
| <b>Printing head position sensor</b>    | Micro switch                                                                                                                                                                                                             |
| <b>Paper exists detection</b>           | Photoelectric sensor                                                                                                                                                                                                     |
| <b>Printing Speed</b>                   | 127 mm / sec (max); 50.8mm/sec (min)                                                                                                                                                                                     |
| <b>Printing Width</b>                   | 16 mm ~ 82 mm                                                                                                                                                                                                            |
| <b>Media</b>                            | Media Type: Paper roll, sticker, label fold, etc.<br>Media diameter: Inner dia:25mm; Outer dia:                                                                                                                          |
| <b>Internal font</b>                    | FONT 0 to FONT 8; Commonly used in single-byte fonts                                                                                                                                                                     |
| <b>Enlargement &amp; rotation</b>       | 1 to 10 times enlargement in both directions; 0 Degree , 90 Degree, 180 Degree, 270 Degree, 360 Degree rotation                                                                                                          |
| <b>Paper off type</b>                   | Tear off & peel off                                                                                                                                                                                                      |
| <b>Memory</b>                           | 2MB Flash Rom, 2MB DRAM                                                                                                                                                                                                  |
| <b>Image</b>                            | Monochromatic PCX, BMP image files can be load to FLASH, DRAM                                                                                                                                                            |
| <b>Barcode</b>                          | CODE128, EAN128, ITF, Code39, Code93, EAN13, EAN13+2, EAN13+5, EAN8, EAN8+2, EAN8+5, CODABAR, POSTNET, UPC-A, UPCA+2, UPCA+5, UPC-E, UPCE+2, UPCE+5, CPOST, MSI, MSIC, PLESSEY, ITF14, EAN14, PDF417, QR CODE, DATMATRIX |
| <b>Interface</b>                        | USB + RS232 + LAN or USB                                                                                                                                                                                                 |
| <b>Power</b>                            | Input: 24VDC, 2.5A                                                                                                                                                                                                       |
|                                         | Operating Temperature: 5 Degree C to 45 Degree C                                                                                                                                                                         |

|                    |                                                                                                                                                                  |
|--------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Environment</b> | Storage Temperature: -40 Degree C to 55 Degree C<br><br>Operating Humidity: 20% ~ 80%, non-condensing,<br>Free air<br>Storage Humidity: <=93%(40 Degree C), non- |
| <b>Dimension</b>   | Size: D220mm * H148mm *W150mm                                                                                                                                    |