

先进的设计理念、持续的创新设计、个性化的专利产品，满足不同客户的需求

Advanced designing thoughts, Technical innovation and new products development corresponded with all kinds of need



KC1000-019 技术规范 SPECIFICATIONS	
外形尺寸 External Dimension	1150*1150*1135
容 积 Capacity	1000L
人孔直径 Manhole Diameter	450mm
叉槽高度 Fork Height	78mm
罐体壁厚 Shell Wall Thickness	2.28mm
排 料 阀 Outlet Valve	DN50
自 重 Tare Weight	170Kg
最大总重 Max. Mass Weight	2770Kg
仓储堆码 Stacking in Warehouse	3层 (High)
运输堆码 Stacking in Transport	1层 (High)

特点 SPECIAL FEATURES
1、认证 (Approval) : UN31A/Y - IMDG 2、罐体主材 (Shell Wall Material) : SUS304, 3、密封材料 (Sealing Material) : EPDM/PTFE 4、排料装置 (Outlet Valve) : 二片式球阀 (2 Piece Ball Valve) 5、安全阀 (Relief Valve) : Pressure Setting 0.21Bar 6、空箱集装箱装载 (Container Loading) : 40 Unit/40HQ or 40GP 7、装载物 (Loading Goods) : 适于液态的, 密度 ≤ 2.6 的 UN II, III类的危险品, (Suitable for Liquid Hazardous Goods, of Density less than or Equal to 2.6 of the UN II、III Group)