



BAOWANXIANG

Innovation, Better Life

BAOBI®



BAOBI Printer BB787S

Two Rolls Loading for labels & wristbands:

Choose Upper Roll for label or wristband

Choose Down Roll for label or wristband

One Roll for label ,another Roll for wristband

Or Two Rolls for labels

Or Two Rolls for wristbands

Select Upper Roll Printing or Down Roll Printing with DRIVER Setting

Or Select Upper Roll Printing or Down Roll Printing

by Switching Keyboard Buttons



Function & Feature

• Direct thermal printing with maximum width of 108mm, 300dpi resolution enables it to print all sorts of one-dimensional barcodes and 2D barcodes with high precision.

• Two Rolls for labels or wristbands printing with easy switch button for any selection. Patented design of printing path with open button makes it more easier to fix paper jam.

• Open printer body design supports labels or wristbands loading without limitation of roll size. Clear cover available for anti dust and paper delivering observation.

China Invention Patent

ZL201510932552.0 / ZL201410425872.2 / ZL201410424971.9 / ZL201410424995.4 / ZL201410424532.8

China Utility Model Patent

ZL201420485041.X / ZL201420485883.5 / ZL201420485060.2 / ZL201420484629.3 / ZL201420485372.3 / ZL201420485020.8 / ZL201420485043.9 / ZL201520619887.2 / ZL201521042940.3 / ZL201521041601.3 / ZL201521039679.1 / ZL201521043015.2 / ZL201521042968.7 / ZL201521042938.6 / ZL201521041592.8 / ZL201521041632.9 / ZL201521041992.9 / ZL201521041736.X / ZL201521041748.2 / ZL201521041856.X

China Design Patent

ZL201530527887.5 / ZL201530527864.4 / ZL201530527870.X / ZL201430307852.6 / ZL201530256892.7 / ZL201530308974.1

Applications

Health Care

• Sample Tracking / Drug Management / Infusion Management / Patient Identification

Service&Leisure

• Water Park / Amusement Park / Concert / Cruise / Hotel / School Tickets Or Wristbands Printing

Retail

• Assets Management / Sales & Storage Management / Commodity Label Printing

Manufacturing / Logistics / Warehouse

• Cargo Tracking / Component Label Printing

Company

• Attendance Management / File Consolidation/ Access Control

These terms and conditions can be varied unilaterally by Baobiwanxiang without notice. Baobiwanxiang reserves the right to make the final interpretation. Product images, presentation and all other information are for reference only. Goods in kind prevail.

BAOBI PRINTER BB787S

SPECIFICATION PARAMETER

The printer specifications in this text are based on the test of printing BAOBI labels / wristbands, for user's reference.
The test result may be different according to actual application setting or use consumable not from Baobiwanxiang.
Baobiwanxiang advocates verifying application from testing.

FEATURES

Thermal printing.
Two Rolls design, easy to switch printing material.
More easier and faster to set.
Equipped with multiple languages.
With LCD, real-time display printing status and quantities.
Label printing software supports the printing of different language texts.
Standard tear paper mode.
Unique energy control of printer head.

PRINTER SPECIFICATIONS

Resolution

300 dpi/12 dots per mm

Print Width

Maximum: 4.25" / 108mm

Minimum : 0.39" / 10mm

Print Speed

Selectable

Standard Speed: 2.5" / 60mm per second

Maximum Speed: 5 ips / 120mm per second

Two Rolls

Upper Roll/Down Roll, selectable.

OPERATING CHARACTERISTICS

Environmental

Operating temperature: 40°F / 4.4°C to 104°F / 40°C

Storage temperature: -40°F / -40°C to 140 °F / 80°C

Operating humidity: 20%-85% non-condensing

Storage humidity: 5%-85% non-condensing

Electrical

Universal power supply(PFC compliant) 100-240VAC,
50-60Hz (60 Watts) External Power Supply

Physical Characteristics

Width: 225mm

Height: 306mm

Depth: 345mm

Weight(N.W): 3.11kg

These terms and conditions can be varied unilaterally by Baobiwanxiang without notice. Baobiwanxiang reserves the right to make the final interpretation. Product images, presentation and all other information are for reference only.
Goods in kind prevail.

Baobiwanxiang Technologies Co., Limited

Add:Bldg#D, Xinhe Industrial Park, Huashan Sandong Avenue, Huadu, Guangzhou, China(510880)

Tel : 86-20-86780687 86780797 86780787

Fax : 86-20-86780697

E-mail : info@baobiwanxiang.com

www.baobiwanxiang.com/en

BAOBI PRINTABLE ID SOLUTION

Software

Baobi Printer Driver

BBDesigner

Programming

BPL+ (Application Programming Interface)

Networking /Connectivity

USB 2.0 interface

Ethernet 10/100 interface

Wireless 802.11 b/g (Optional)

Font and Graphic

Support user-defined fonts and graphics-including custom logo

Font and Barcode rotation : 90, 180, 270 degrees

Barcode

Linear Barcode: Code 39, Code 128A,B&C , UCC/EAN-128, Code 93, Codabar, Interleaved 2 of 5, UPC-A, UPC-E, UPC-A with 2 and 5 add on, UPC-E with 2 and 5 add on, EAN 13, EAN 8, EAN 13 with 2 and 5 add on, EAN 8 with 2 and 5 add on, Postnet, Standard 2 of 5, Industrial 2 of 5, LOGMARS, MSI, Codabar and GS1 DataBar(formerly RSS), Code 11, China Post

2-Dimensional Barcode: PDF-417, Maxicode, DataMatrix, QR code, Aztec

Accessories

Software CD Disk

(BBDesigner / Baobi Printer Driver)

Warranty Card

USB Port Cable

Power Adapter

Power Cord

BAOBI Label Holder WH01(Optional)

