



Shenzhen TPS Technology Industry Co., Ltd
 Whatsapp&Skype&Wechat: +0086-15013594651
 Email: Emilyzhou@sztpswkn.com
 Website: https://sztpswkn.en.alibaba.com

Address: 302 Room, #B building, Zhongkenuo Industrial Park, Hezhou, Xixiang Street, Baoan district, Shenzhen, 518106, China.



K1095-10.95inch 4G Android Tablet PC Quote -MTK8788

Hardware Specifications

CPU	CPU	MTK8788 Cortex-A73, Cortex-A53 Octa Core 2.0GHz
	GPU	Mali-G57-3EE-1core 650MHz ES3.2
RAM	DDR	6GB
Memory	EMMC	128GB
Display	LCD	10.95inch 1200*2000IPS 2k Screen
Touch Screen	TP	Capacitive multi-touch
Camera	Front	8.0mp
	Back	13.0mp
Horn	BOX	8Ω/1W *2
Motor	support	Built-in column vibrating motor
MIC	support	Built-in capacitive mic
Type-C	data	Connect the PC or OTG
	charging	Type-C charging, 5V/2A
Docking	Keyboard port	USB2.0
Earphone	support	1*3.5mm 4 call headphones with MIC
Battery	Lithium ion battery	3.8v/8000mAh Lithiumion battery
Sensor	Gravity	Support 3 - D G-sensor games and applications
	Light/distance sense	Support distance/light sensing (non-standard)
SIM Card slot	support	Nano sim *2 or Nano sim+TF
Fingerprint Scanner	support	1*Fingerprint Scanner
Positioning	support	GPS /GLONASS/BDS
Wireless network	WiFi/BT	802.11b/g/n/ac2.4G/5G +BT5.0
Communication	4G+3G+2G	Support:GSM:(B2/B3/B5/B8) ;WCDMA:(B1/B2/B5/B8);TD-SCDMA:(B34/B39) ; LTE-TDD:(B38/B39/B40/B41); LTE-FDD:(B1/B2/B3/ B4/ B5/B7/B8/B12/B17/B20/B25/B26/B28/B66)

Software Specifications

OS	OS	Android 12.0, 13.0
Software	Video Format	H.264&H.265 &MP4 1080p 60 fps , H.263 16CIF 30 fps, VP8&VP9 1080p 60fps
	Audio format	MP3/AAC/AAC+/AMR-NB
	Image Format	JPG, JPEG, GIF, BMP, PNG
	E-books	TXT, EPUB, PDF,WORD,EXCEL,POWERPOINTS
	using	Google , Chromeme, Gmail, Maps, YouTube, Photos, Messages, Calculator, Clock, Duo, Sound Record, Play Store, Camera, YT Music
	Office Software	EPUB, WORD, EXCEL, POWERPOINT, PDF, TXT
	Supported language	Multiple languages
	Certificate	FCC, CE, ROHS

Other Specifications

Shell	Shell	Hardware + plastic hot melt
	Size	258.9*163*7.9mm
	weight	520g
Environmental Requirements	Operating temperature	0-45 degrees Celsius
	Working humidity requirements	10%-90% condensation free
	Storage temperature	-10 to 60 degrees Celsius
	Storage humidity Requirements	5%-90% free of condensation