

### Commercial POU Water Fountain

ITEM		SPECIFICATIONS		
Model		YLR-600A	YL-600A	YL-600AW (Wall mounted or desktop)
Rated Voltage		220-240V/ 50H/110-120V /60Hz/127V/60Hz		
Rated Power	Hot	800W	/	/
	Cold	200W (Force cooling system)		
Cold/Hot	Compressor Type	Hermetic, with overload protector, R134a		
	Hot Water Tank Capacity	5.0L (1.3Gallon)	/	/
	Cold Water Tank Capacity	4.2L (1.1Gallon)	4.2L (1.1Gallon)	3.2L (0.8Gallon)
	Heating Capacity	Inner hot 10L/Hr (2.6Gallon) at 90-95°C (277-293°F)	/	/
	Cooling Capacity	20L/Hr (5.3Gallon) at 8-12°C (25-37°F), against ambient temperature 25°C (77°F)		
Filter System		Available for selection		/
Faucet		2 decompression faucets & 1muzzles	1decompression faucets & 1muzzles	1 decompression faucets &1 muzzles
Pressure Device		Include decompression valve		
Product Weight		28.5 kg (62.8lb)	24.5kg (54lb)	18kg (39.7lb)
Product Boxed Weight		31kg (68.3lb)	25.5kg (56.2lb)	19kg (41.9lb)
Product Dimensions		430 (D) x 305 (W) x 1220 (H)mm 17.0" (D) x12.0"(W) x 48"(H)		430 (D) x 305(W) x 700 (H)mm 17.0" (D) x12.0"(W) x 27.6"(H)
Product Boxed Dimensions		450(D) x 320(W) x 1110(H)mm 17.7" (D) x12.6"(W) x 43.7"(H)		450(D) x 320(W) x 580(H)mm 17.7" (D) x12.6"(W) x 22"(H)
Loading Quantity		20' Container: 180 Units 40' Container: 360Units		20' Container: 360 Units 40' Container: 720 Units
Required Water Pressure		0.07-0.5Mpa		
Required Water Source		City water		
Unit price				
Min order		1*20" container		

YLR-600A



YL-600AW

YL-600A