

Specification

Outlook	Model	H5812 Mini Hunting CAM
	Highlight	•8 Mega pixels Digital Camera •4K/10FPS,2.7K/20FPS,1080P/30FPS, video •16 months Standby time •20m range of IR flash •Triggering time: 0.2 Second • 20m triggering distance •Spray-water protected(IP protection class66)
	Application Sceneries	Field hunting, observation and investigation of animal activity rules, automatic monitoring of plants, climate and environment, monitoring of farms, orchards, construction sites, supermarkets, warehouses and villas etc
	Image sensor	8 Mega pixels Digital Camera
	Still image size	20MP:5200x3900(interpolated);16MP:4608x3456(interpolated);12MP:4000x3000(interpolated);8M:3264x2448;5M:2592x1944;3M:2048*1536; 1M:1280*960;
	Video clip	3840x2160/10fps ; 2688x1520/20fps ; 1920x1080/30fps ; 1280x720/60fps ; 1280x720/30fps ; 720x480/30fps; 640x480/30fps;320x240/30fps
	File format	JPG/AVI
	Lens angle	F/NO 1.6; FOV=70°; Auto IR filter
	LCD Display	2.0" TFT 960*240
	Memory	External memory(TF card, Class 6 Above, up to 512GB)
	Operation keypad	6 Keys
	The number of IR lamp	2PCS (High power /850nm)
	Range of IR flash	20m
	Triggering distance	20m (Below 77°F/25°C at the Normal Level)
	Prep PIR sensing angle	60°
	Triggering time	0.2 Second(When using the 4G TF card);
	Trigger interval	5sec. - 60min;Programmable
	Shooting numbers	1~3;
	Video Length	3sec-10Minutes ; Programmable
	Effectiveness	Daytime:1m -infinite;Night time:1.5m-20m
	Camera+Video	First take Picture then Video
	Time stamp	On/Off;include serial No.,temperatureand moon phase
	Time lapse	On/Off; Time Lapse Programmable
	Compressed video	TL Video Time Laps 3 Second ~ 24Hours
	Periodic Shot	Time Laps 1 Second ~ 24Hours
	Device serial No.	4 digits or 26 alphabets set by yourself
	Build-in Microphone/Speaker	Yes
	Auto-distinguish images	Color images in daytime/black & white night images
	Automatic screen saver	Automatic screen saver in 2 minutes while no keypad controlling
	PC interface	Mini USB2.0
	Power supply	4xAAA ; external 6V power supply,at least 2A
	Standby time	approx.8 months
	Lockable	Optional
	Password protection	4-Digit Numbers
	Spray-water protected	Spray-water protected
	Operating temperature	-7°C to +40°C
	Storage Temperature	-20°C to +60°C
	Dimensions & Weight	104*74*43mm/142g