

Type	XJ-65	XJ-85	XJ-115	XJ-150	XJ-200	XJ-250
Form of screw&screw thread	Double-head equaldpth convergent type	Double-head equidistant unequaldepth ttype	Double-head convergent type	Double -head unequaldepth convergent type	Double-head convergent type	Double-head convergent type
Screw diameter(mm)	65	85	115	150	200	250
Length-diameter ratio of screw	4	4.3	4.8	4.43	4.35	4.5
Compression ratio		1.3	1.3	1.34		
Screw rational speed(r/min)	20/2735/47	28/40/56/80	33/46/60	27-81	22.4-67.2	19.7-59.1
Motor power(KW)	7.5	10/14	22	Frequency control 18.3-55 Moter	Frequency control 25-75 Moter	Frequency control 33.3-100 Moter
Production capacity(kg/h)	50-80	62-270	100-420	700-1200	2200	3500
Stream pressure(Mpa)	0.3-0.4	0.4-0.6	0.4-0.6	0.6-0.8	0.6-0.8	0.6-0.8
Cold water pressure(Mpa)	0.2-0.3	0.2-0.3	0.2-0.3	0.2-0.3	0.2-0.4	0.2-0.4
Compressed air pressure					0.6	0.6
Size(LXWXH) (mm)	1630x604x1050	2050x700x1200	1630x604x1050	3411x814x1470	4564x1800x1750	4950x1150x1483
Weight(kg)	1200	2500	3000	5000	7300	11400