



Kiosk embedded printer HCC-EU805

General

HCC-EU805 printer is a new thermal line panel printer, with drop-in paper easy loading, auto cutter, Black label detection, faster and more reliable. HCC-EU805 printer easy operation, applications widely, especially to queue machine, POS for bank and the business of all kinds of needed docs to print.

Features

- 80mm thermal receipt printer, with Paper Stand
- Anti-blocking paper and anti-pull paper function
- Compatible with ESC/POS command
- Long printing life
- Indicator light function

Specification

Print	Printing Method	Thermal Line
	Printing Speed	150 mm/s
	Resolution	8 dots/mm, 576 dots/line
	Effective Printing Width	72mm
Character	Character Set	ASCII, GB18030(Chinese), BIG5
	Print Font	ASCII:12×24;8×16; 9×17
Paper Spec	Paper Type	Thermal paper
	Paper Width	79.5±0.5mm(with SP-MF1), 82±0.5mm
	Paper Thickness	0.06~0.08mm
	Paper Roll Diameter	More than: 80.0mm
Reliability	MCBF	1 million lines
Barcode	1D:UPC-A, UPC-E, EAN-13, EAN-8, CODE39, ITF25, CODEBAR, CODE93, CODE128 2D: PDF417, QRCODE, DATAMATRIX	
Bitmap print command	Support printing bitmaps with different density and downloaded graphics.	
Characters print command	Support the double width and height printing of ANK characters, self-defined characters and Chinese; characters lines spacing can be adjusted	
Emulation	ESC/POS, CPCL(option)	
Driver	Windows 98 / ME / 2000 / NT / XP / 2003 Server/Vista/Win7/Win8	

Interface		USB/RS232
Paper Supply Method		Manual paper loading
Power Supply (Adapter)		DC24V±10%, 2A
Power Plug interface		VH3.96-4P
TPH		100KM
Auto cutter	Type	Guillotine
	Life	1,000,000
	Cutting Method	Partial Cut/ Full cut
Physical	HCC-EU804U	251.5*120*109.3mm
	HCC-EU804MF(with SP-MF1)	274.3*120*109.3mm
	Operating Temp/Humidity	0~50℃ /10%~80%
	Storage Temp/Humidity	20~60℃ /10%~90%

Picture



Shenzhen HCC Technology Co., Ltd.

 Address: Rm. 201, 2/F, Bldg. 8, Changyuan New Material Port, No. 2 Gaoxin C. 1st Ave., Yuehai St., Nanshan Dist., Shenzhen, P.R.China
 Post Code:518057 Tel:86-755-86655162 Fax:86-755-8606-9640 Web:www.szhcct.com