

65W desktop GaN charger with 2C2A ports Specifications	
Model No.	P1865
Input	
Normal voltage range	100Vac - 240Vac
Input frequency range	47Hz-63Hz
Rated input frequency	50Hz/60Hz
Max input AC	1.8A max at full load condition
Output	
use 1 port	
USB-C1/C2	PD 65W: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20/3.25A, (PPS: 3.3-11.0V 5A)
USB-A1/A2	QC 36W: 5V/3A, 9V/3A , 12V/3A, 20V/1.8A
use 2 ports	
C1+C2	C1 PD 45W+C2 PD 20W
C1+A1/A2	C1 PD 45W+A1/A2 QC 18W
C2+A1/A2	C2 PD 45W+A1/A2 QC 18W
A1+A2	A1 QC 8.5W: 5V/1.7A + A2 QC 8.5W: 5V/1.7A
use 3 ports	
C1+C2+A1/A2	C1 PD 30W+C2 PD 20W+ A1 QC 18W
Charging Protocol & Intelligent Identification	Support PD3.0 or PD2.0 ,QC3.0/QC2.0,Support PPS,AFC,SCP,FCP, Support AppleBC1.2,Support DCP-1.5A
Output power	65W Max
Output Ripple	≤150
Physical specifications	
Color	Black/White or customized
Shell Type	Plastic
Shell material	PC (Temperature resistance: 120°C) PC material meets the requirement of spherical pressure test.
LED Indicators	Indicate white led color when charging
Product size	85*85*23.3mm
Product weight	200g
Storage Temperature	-20°C to 80°C