

		Shenzhen Zecre Technology Co., Ltd Add.: 5th floor, B Building, Debaoli Industrial Park, Bantian, Longgang, Shenzhen Tel.: 0755-28367890 Mob.:13332935176 E-mail: anna.ruan@zecre.com Website: www.zecre.com	
Model		PH730	
Key Features			
	Image Sensor	1/2.7-Inch 3-Megapixel CMOS Sensor	
	Stand-by Time	Approx 8 months	
	Range of IR Flash	120 degree,Range of IR flash 20M	
	Trigger Times	0.2-0.6 sec super fast trigger times	
	HD Quality	12MP 1080P quality images & videos	
	Black Low Glow 940NM IR LED	42pcs 940nm Black Low Glow covert infrared flash LED provides a 80 feet flash range in the dark, which makes it a stealthy unit that does not intrude into the natural habitat.	
Specification			
	Image sensor	1/2.7-Inch 3 Megapixel CMOS Sensor	
	Lens	Focal Length=7.2mm F/NO=2.8 View Angle=55°	
	Storage Media	SD Card, up to 32GB	
	Mode	Photo Video Photo*Video	
	Photo resolution	12.0 Mega pixels 8.0 Mega pixels 5.0 Mega pixels 3.0 Mega pixels 1.0 Mega pixels	
	Photo Series	1Photo 2 Photo in series 3 Photo in series	
	Video resolution	1080P: 1920*1080 720P: 1280*720 D1: 720*480 VGA: 640*480 QVGA:320*240	
	File format	JPEG/AVI(H.264)	
	IR Filter	Full Automatic IR Filter	
	TFT LCD Display Screen	48x35.69mm (2.36");480(RGB)*234DOT; 16M color	
	Main PIR Angle	40°	
	Side PIR Angle	L: 30° R: 30°	
	Dual PIR Angle	120°	
	PIR Sensing Distance	80ft/25 meters	
	Number of IR LED	42 IR LEDs	
	Max Night Vision Lighting Distance	80ft/25 meters	
	Trigger Times	0.2-0.6 sec super fast trigger times	
	Low Battery Auto Power Off	support	
	Triggering Interval	5second ~ 60mins (default 60 sec)	
	Date Time Imprint	Yes	
	Moon Phase Imprint	Yes	
	Ambient Temperature Imprint	Yes	
	Serial NO. Imprint	Yes	
	Exposure	Auto	
	Pass Word Set	4 bit, Digits and 26 alphabet set by yourself	
	Device Serial No. Set	4 bit, Digits and 26 alphabet set by yourself	
	Time Switch	support	
	Periodic shot	0Second~24Hours	
	Stand-by current	Lower than 0.2mA	
	Stand-by Time	Approx 8 months	
	Built-in MIC	Yes	
	Built-in Speaker	Yes	
	Interface	External: TV out (NTSC/PAL,MiniUSB); MiniUSB; SD Card Holder; 6V DC Power Jack	
	Fix Method	Bandage, Iron Bracket (1/4 Inch Standard Interface)	
	Operation Temperature	-20 - 60°C	
Operating humidity	5% ~ 90%		
Power Source	4-8 AA Battery DC :6V-1.5A		
Water proof Standard	IP66		
Language	English/Deutsch/Dansk/Suomi/Svenska/Espanol/ Francais/Italiano/Nederlands/Portugues/Chinese		
Security authentication	CE, ROHS, FCC, WEEE		
Packing List			
	Product size	136 x 98 x 76mm	
	Color box size	180*122*104mm	
	Net weight	270g	
	Shipment box size	20pcs/ctn 37.5*31.8*43.5cm	
	Accessories list	MiniUSB Cable, User manual, Strap, Wall mount, Screws	