

SW-110N4 Technical	
Compatible with	
Channel	
PMPO output	
Source input	
Device supports	
Bluetooth Version	
Bluetooth Range	
Frequency response:	
S/N ratio:	
Distortion (THD):	
Output Power:	SW:
	BAR:
Separation:	
Input sensitive:	
Hum-noise output:	
Satellite impedance:	
Subwoofer impedance:	
Speaker(Driver) size:	BAR:
	SW:
Dimension:	BAR:
	SW:
Power consumption (St.By):	
Power consumption:	
Power supply:	
Remote control	
Remote control Battery	
Remote control range:	
Remote control angle	
Accessories	

Specification(FT3129*2+SMPS)
TV, DVD, PC, Laptop, Tablet, Mobile, MP3, player etc...,
2.1
/
USB/SD/BT/AUX/OPTICAL/HDMI(ARC)
USB/SD/MMC
Dual mode bluetooth V5.0
10M(Without Barrier)
35Hz - 20KHz
≥68dB
≤0.3% (1W 1KHz)
70W X 1
20W X 2
≥ 45db
600mV
≤ 3.0 mV
4Ω
4Ω
2" X 2
6.5" X 1
W800*D87*H87mm
W250*D250*H394mm
≤2.5W
70W+40W
AC100-240V 50/60Hz_ DC19V3.0A + DC24V4.0A
Yes
/
5m
30°
User Manual, Warranty Card , Audio Cable, Remote control