Daisy Xiang-Sales Manager
FIRST INDUSTRIAL DEVELOPMENT CO.,LIMITED
T: +86 577 6256 8230 F: +86 577 6256 8230
Mobile: +86-133 8858 7626(whatsapp, wechat)
Skype: daisyxiang123
E-mail:daisy@firstcooler.com,info@firstcooler.com
www.firsth2o.com

COMPRESSOR WINE COOLER QUOTATION

Article No.	RHC-SW-12	RHC-SW-24	RHC-SW-28	RHC-SW-38	RHCSW-43	RHC-SW-66	RHC-SW-75	RHC-SW-126	SW-137	SW-180	SW-192
Product photo											
Bottle	12	24-35	28-40	38-50	43-53	66-80	75-95	129-140	137-150	181-210	192-220
Volume	35	80	80	125L	125L	190L	190L	360L	360L	480L	480L
Temperature Zone	Single	Dual	Single	Dual	Single	Dual	Single	Dual	Single	Dual	Single
Standard Wood Shelf with Sliding shelf	3pcs	5pcs	4pcs	7pcs	4pcs	7pcs	4pcs	6pcs	7pcs	8pcs	8pcs
Gas	R600a/R134A	R600a/R134A	R600a/R134A	R600a/R134A	R600a/R134A	R600a/R134A	R600a/R134A	R600a/R134A	R600a/R134A	R600a/R134A	R600a/R134A
Type of cooling	Direct cooling	compressor with FAN cooling	compressor with FAN cooling	compressor with FAN cooling	compressor with FAN cooling	compressor with FAN cooling	compressor with FAN cooling	compressor with FAN cooling	compressor with FAN cooling	compressor with FAN cooling	compressor with FAN cooling
Compressor Type	Baixue/Qianjiang/Hua...	Baixue/Qianjiang/Huayi	Baixue/Qianjiang/Huayi	Baixue/Qianjiang/Huayi	Baixue/Qianjiang/Huayi	Zanussi/Huayi	Zanussi/Huayi	Zanussi/Huayi	Zanussi/Huayi	Zanussi/Huayi	Zanussi/Huayi
Climate type	ST	ST	ST	ST	ST	ST	ST	ST	ST	ST	ST
Electricity protection grade	I	I	I	I	I	I	I	I	I	I	I
with Heater	No	Yes	No	Yes	No	Yes	No	YES	NO	YES	NO
Body Color	Black Casing	Black Casing	Black Casing	Black Casing	Black Casing	Black Casing	Black Casing	Black Casing	Black Casing	Black Casing	Black Casing
LED light	Blue	Blue	Blue	Blue	Blue	Blue	Blue	Blue	Blue	Blue	Blue
Layer for glass	2	2	2	2	2	2	2	2	2	2	2
Anti-UV and Glass	Brown Glass	Brown Glass	Brown Glass	Brown Glass	Brown Glass	Brown Glass	Brown Glass	Brown Glass	Brown Glass	Brown Glass	Brown Glass
Power cord & plug	provide relevant standard of different	provide relevant standard of different markets	provide relevant standard of different markets	provide relevant standard of different markets	provide relevant standard of different markets	provide relevant standard of different markets	provide relevant standard of different markets	provide relevant standard of different markets	provide relevant standard of different markets	provide relevant standard of different markets	provide relevant standard of different markets
Nominal voltage/Frequency	20-240V/50HZ, 115V/60H	220-240V/50HZ, 115V/60HZ	220-240V/50HZ, 115V/60HZ	220-240V/50HZ, 115V/60HZ	220-240V/50HZ, 115V/60HZ	220-240V/50HZ, 115V/60HZ	220-240V/50HZ, 115V/60HZ	220-240V/50HZ, 115V/60HZ	220-240V/50HZ, 115V/60HZ	220-240V/50HZ, 115V/60HZ	220-240V/50HZ, 115V/60HZ
Rated power(W)	60	117	117	117	117	120	120	120	120	170	170
Power consumption in 24 hours	0.5KW	0.5KW	0.5KW	0.74KW	0.58KW	1.0KW	0.81KW	1.3	1.3	1.4	1.4
Ambient temperature	0-38°C	0-38°C	0-38°C	0-38°C	0-38°C	0-38°C	0-38°C	0-38°C	0-38°C	0-38°C	0-38°C
Temperature range(two zone)	3-22°C/3-22C	3-22°C/3-22C	3-22°C	3-22°C/3-22C	3-22°C	3-22°C/3-22C	3-22°C	3-22/3-22	3-22°C	3-22/3-22	3-22°C
Range of inside cabinet humidity	>60%RH	>60%RH	>60%RH	>60%RH	>60%RH	>60%RH	>60%RH	>60%RH	>60%RH	>60%RH	>60%RH
Body size(MM)	395X480X505	395X480X840	395X480X840	395X580X1020	395X580X1020	595X580X1020	595X580X1020	595X580X1640	595X680X1840	595X680X1840	595X680X1840
Packing size(MM)W*D*H	455*550*550	455*550*940	455*550*940	455*645*1100	455*645*1100	650*650*1130	650*650*1130	650*650*1740	650*650*1740	665*755*1940	665*755*1940
20'gp container load(pcs)	180	102	102	90	90	54	54	27	27	27	27
40'gp container load(pcs)	364	204	204	170	170	108	108	54	54	54	54
40'HQ container load(pcs)	364	306	306	220	220	108	108	4	54	54	54
Net weight(KG)	25	34	34	43	43	53.5	53.5	112	112	112	112
Gross weight(KG)	30	36.5	36.5	46	46	56	56	117	117	117	117
Door style	Black Door	Black Door	Black Door	Black Door	Black Door	Black Door	Black Door	Black Door	Black Door	Black Door	Black Door
Door Lock											
Three Layer Glass door											
S.S door											
Approval	cETL,ETL,GS,CE,CB	cETL,ETL,GS,CE,CB	cETL,ETL,GS,CE,CB	cETL,ETL,GS,CE,CB	cETL,ETL,GS,CE,CB	cETL,ETL,GS,CE,CB	cETL,ETL,GS,CE,CB	cETL,ETL,GS,CE,CB	cETL,ETL,GS,CE,CB	cETL,ETL,GS,CE,CB	cETL,ETL,GS,CE,CB