

	1	2	3	4	5	6	7	8	9																
G	RoHS									G															
F			①LG016 ②LG019 ③LJ010 ④LG021 ⑤LG020 ⑥LJ003 ⑦LJ011							F															
E	<table><tr><td>序号</td><td>外壳</td><td>颜色</td></tr><tr><td>A</td><td>LG016 -A</td><td>9005</td></tr><tr><td>B</td><td>LG016 -B</td><td>9001</td></tr></table>		序号	外壳	颜色	A	LG016 -A	9005	B	LG016 -B	9001								E						
序号	外壳	颜色																							
A	LG016 -A	9005																							
B	LG016 -B	9001																							
D	<table><tr><td>C</td><td>LG016 -C</td><td>5005</td></tr><tr><td>D</td><td>LG016 -D</td><td>4004</td></tr><tr><td>E</td><td>LG016 -E</td><td>6002</td></tr><tr><td>F</td><td>LG016 -F</td><td>8011</td></tr></table>		C	LG016 -C	5005	D	LG016 -D	4004	E	LG016 -E	6002	F	LG016 -F	8011	备注: 1. 主体: 锌合金, 表面处理: 铜底6-8um, 镍2.5um以上, 2. 绝缘体: PA66 3. 外壳: PBT, 参考扣位表 4. 铜圈: 铜, 表面处理: 镀镍60迈以上, 5. 中心针: 全部表面底层镀镍0.76~2um, 接触区域 表层镀金0.125um以上. 6. 电气性能: 阻抗50 OHM, 工作电压500伏交流 7. 机械性能: 工作温度-40° 至 105° 8. 组装主体于5秒内需能承受15N轴向力. 外壳于5秒内 需能承受110N轴向力							D			
C	LG016 -C	5005																							
D	LG016 -D	4004																							
E	LG016 -E	6002																							
F	LG016 -F	8011																							
C	<table><tr><td>G</td><td>LG016 -G</td><td>7031</td></tr><tr><td>H</td><td>LG016 -H</td><td>4003</td></tr><tr><td>J</td><td>LG016 -J</td><td>1001</td></tr><tr><td>K</td><td>LG016 -K</td><td>1027</td></tr><tr><td>L</td><td>LG016 -L</td><td>6018</td></tr></table>		G	LG016 -G	7031	H	LG016 -H	4003	J	LG016 -J	1001	K	LG016 -K	1027	L	LG016 -L	6018								C
G	LG016 -G	7031																							
H	LG016 -H	4003																							
J	LG016 -J	1001																							
K	LG016 -K	1027																							
L	LG016 -L	6018																							
B	<table><tr><td>M</td><td>LG016 -M</td><td>2003</td></tr><tr><td>O</td><td>LG016 -O</td><td>6027</td></tr></table>		M	LG016 -M	2003	O	LG016 -O	6027								B									
M	LG016 -M	2003																							
O	LG016 -O	6027																							
A					OPERATION		DRAW	Lu jin ying	SCALE	FIT	HECON 东莞市禾康电子有限公司 DONGGUAN HECON ELECTRONICS CO.,LTD		A												
					X.X	±0.30			UNIT	mm															
					X.XX	±0.20	CHECK		SIZE	A4															
	A0		NEW DRAWING		X.XXX	±0.10			SHEET	1/1	PART NO. HC-WH--HSD-F-F-200-C01														
	REV	DATE	MODIFICATION DESCRIPTION		CHANGE	Angle ±3°	APPROVE		PROJ.		TITLE: HSD Female To Female L=200mm														
	1		2		3	4	5		6		7	8	9												